





Unleash your full gaming potential with the 240Hz G2471HS Red Eagle guaranteeing 0.3ms MPRT

Gain the competitive edge you need to unlock your full gaming potential with the 24" G2471HS monitor with FHD (1920x1080) resolution. Featuring an ultra-fast 0.3ms MPRT and a 240Hz refresh rate, this monitor ensures smooth gameplay. Compatible with NVIDIA G-SYNC so you can make split second decisions and forget about ghosting effects or smearing issues. The ability to adjust brightness and the dark shades with the Black Tuner delivers greater viewing performance in shadowed areas and the IPS panel technology guarantees superb image quality.

Available also with height adjustable stand : G-Master GB2471HS-B1 (1920x1080) a n d G-Master GB2471HSU-B1 (1920x1080)



Fast IPS

The lightning-fast IPS panel with Full HD 1920x1080 resolution delivers ultra-smooth gameplay and vibrant, true-to-life colours with exceptional accuracy and wide viewing angles.



240Hz

With 240Hz refresh rate the force is with you! Make split second decisions and be sure the image on the screen is always sharp and smooth.



Diagonal	23.8", 60.5cm
Panel	Fast IPS, haze haze 25%
Native resolution	1920 x 1080 @240Hz (2.1 megapixel full HD, DisplayPort)
Aspect ratio	16:9
Panel brightness	350 cd/m ²
Static contrast	1000:1
Advanced contrast	80M:1
Response time (MPRT)	0.3ms
Viewing zone	$horizontal/vertical: horizontal^\circ/vertical\ horizontal^\circ,\ right/left:\ 0^\circ/0^\circ,\ up/down:\ 0^\circ/0^\circ$
Colour support	16.7mln 8bit
Horizontal Sync	30 - 285kHz
Viewable area W x H	527 x 296.5mm, 20,7 x 11,7"
Pixel pitch	0.275mm
Colour	matte, black



02 INTERFACES / CONNECTORS / CONTROLS

Signal input	HDMI x2 (v.2.0, max. 1920 x 1080 @240Hz) DisplayPort x1 (v.1.2, max. 1920 x 1080 @240Hz)
HDCP	yes
Headphone connector	ves



03 FEATURES

Blue light reducer	yes
Flicker free	yes
Adaptive Sync support	G-SYNC - 1920 x 1080 @48-240Hz, DisplayPort Only
Extra	i-Style Colour
HDR	Yes, HDR10 Ready
OSD languages	EN, DE, FR, ES, IT, PT, RU, JP, CZ, NL, PL
Control buttons	power switch, joystick, menu (center), up / signal select, down / shortcut, left / volume -, right / volume +
User controls	picture adjust (contrast, brightness, OverDrive, HDR, Adaptive Sync, night mode, blue light reducer, Motion Blur Reducer, gamma), input select (input source, auto/manual, DP, HDMI1, HDMI2), audio adjust (volume, mute), store user settings (user modes), colour settings (6-axis, colour temperature, user preset, black tuner), image adjust (i-Style Colour, X-Res Technology, sharpness, HDMI range, Direct Drive Mode, video mode adjust), language, OSD setup menu (OSD H. position, OSD V. position, OSD Time, Opening Logo, Power LED, DDC/ DI Control, USB charge), display information, reset (reset all)
Speakers	2 x 2W
Convenience	Kensington-lock™ prepared, DDC/CI, DDC2B, Mac OSX



MECHANICAL

Display position adjustments	tilt
Tilt angle	21° up; 3° down
VESA mounting	100 x 100mm
Cable management system	yes



Cables	power (1.8m), HDMI (1.8m), DP (1.8m)
Other	quick start guide, safety guide

06 POWER MANAGEMENT


Power supply unit	internal
Power supply	AC AC - AC V, 100/V, 240Hz
Power usage	18W typical, 0.5W stand by, 0.3W off mode

07 SUSTAINABILITY

Regulations	CE, TÜV-Bauart, EAC, PSE, RoHS support, ErP, WEEE, VCCI, REACH, UKCA
Energy efficiency class (Regulation (EU) 2017/1369)	E
REACH SVHC	above 0.1%: Lead
	400.0 0 /0. 2040

08 DIMENSIONS / WEIGHT

Product dimensions W x H x D	540 x 395 x 192.5mm
Box dimensions W x H x D	610 x 126 x 413mm
Weight (without box)	3.4kg
Weight (without stand)	3.1kg
Weight (with box)	5.4kg
EAN code	4948570126415



All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects.

© IIYAMA CORPORATION. ALL RIGHTS RESERVED