

INFORMATION



32" 4K VA panel with USB-C Dock (95W), KVM Switch, LAN and PiP/PbP

The ProLite XB3294UHSCP-B1 is a 32 inch 4K monitor designed to give you more space, sharper detail, and smoother workflows.

Its VA panel with Ultra HD resolution and a 3000:1 contrast ratio delivers crisp, vibrant visuals. A brightness of 350cd/m², 2ms response time, and Adaptive Sync ensure everything stays smooth and clear, whether you're creating content or working with data.

USB-C (95W Power Delivery), HDMI, DisplayPort, and a built-in KVM switch make it easy to manage multiple devices while powering your laptop. PiP (Picture-in-Picture) and PbP (Picture-by-Picture) modes let you view content from two sources at the same time for more efficient multitasking.

The three side borderless design helps you stay focused and supports seamless multi-monitor setups. The height adjustable stand, built-in speakers, and headphone jack provide comfort and convenience throughout your day.

Certified with TCO, TÜV-GS and EPEAT Silver, it's a smart, sustainable choice for any modern workspace.



Easy multi-device control with KVM

Easily switch between multiple computers using one monitor, keyboard, and mouse, making multitasking smooth and efficient.



USB-C dock for tidy desk & easy connectivity

Connect everything with just one cable — handle video, data, and power while keeping your desk clean and organized.



Mini HDMI, your gateway to versatile media

Pair your monitor to laptop, camera, console, or mini PC. Enjoy high-quality video and audio, expand your creative workflow and take your entertainment anywhere.



Multi-screen setup for a panoramic workspace

Connect multiple ultra-slim bezel monitors to create a panoramic workspace, keep your apps in view, streamline multitasking, and boost productivity.

01

DISPLAY CHARACTERISTICS

Design	3-side borderless
Diagonal	31.5", 80cm
Panel	VA
Native resolution	3840 x 2160 @60Hz (8.3 megapixel 4K UHD)
Aspect ratio	16:9
Panel brightness	400 cd/m ²
Static contrast	3000:1
Advanced contrast	80M:1
Response time (GTG)	2ms
Viewing zone	horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89°
Colour support	1.07B 8bit+FRC (sRGB: 99%; NTSC: 93%)
Horizontal Sync	30 - 160kHz
Viewable area W x H	708.9 x 405.7mm, 27.9 x 15.9"
Pixel pitch	0.182mm
Colour	matte, black



INTERFACES / CONNECTORS / CONTROLS

Signal input	HDMI x2 (v.2.1) DisplayPort x1 (v.1.2) USB-C x1 (PD 95W)
USB HUB	x4 (2x Type-A v.3.2 Gen 1 (5Gbps, 4.5W) 2x Type-C (5Gbps, 7.5W))
USB-C DOCK	x1 (Power delivery 95W, LAN, USB v.1.2 (Gen 1, 5Gbit))
HDCP	yes
Headphone connector	yes
RJ45 (LAN)	x1



FEATURES

KVM switch	yes
Blue light reducer	yes
Flicker free	yes
Adaptive Sync support	yes
Extra	i-Style colour
HDR	HDR10
OSD languages	EN, DE, FR, ES, IT, RU, JP, CZ, NL, PL, UA
Control buttons	Joystick: Center: Power/ Menu, Up/ Input Select, Down, Left: i-Style Colour/ ECO/ Blue Light Reducer, Right/ Volume
Speakers	2 x 5W
Convenience	Kensington-lock™ prepared, DDC/CI, DDC2B



Display position adjustments

Height adjustment

Rotation (PIVOT function)

Swivel stand

90°; 45° left; 45° right

Tilt angle 23° up; 5° down

VESA mounting 100 x 100mm

Cable management ye system

05 ACCESSORIES INCLUDED

Cables power (1.85m), USB (1.5m), HDMI, DP (1.85m), USB-C (1.0m)

Other quick start guide, safety guide

06 POWER MANAGEMENT

Power supply unit internal

Power supply AC 100 - 240V, 50/60Hz

Power usage 55W typical, 0.5W stand by, 0.3W off mode

07 SUSTAINABILITY

Regulations TCO Certified, CE, TÜV-GS, EAC, VCCI-B, PSE, RoHS support, ErP, WEEE, REACH, UKCA

Energy efficiency G class (Regulation (EU) 2017/1369)

REACH SVHC above 0.1%: Lead

08 DIMENSIONS / WEIGHT

Product dimensions 713.9 x 448.5 (598.5) x 245.5mm

WxHxD

Box dimensions W x 790 x 510 x 143mm

H x D

Weight (without box) 8.5kg

Weight (with box) 11.8kg

EAN code 4948570126279



© IIYAMA CORPORATION. ALL RIGHTS RESERVED