

DESKTOP MONITORS

Precision meets performance

Work with confidence on the 32" ProGraphic HB3201, a 4K UHD monitor engineered for designers, photographers, and content creators who demand uncompromising visual clarity.



Powered by IPS Black 2.0 technology, it delivers deeper contrast and richer blacks, ensuring every shadow and detail is revealed with stunning precision.

With 99% DCI-P3 coverage and [Pantone Validated](#) colour accuracy, your work translates seamlessly across print, video, and digital platforms. The AGLR anti-glare coating minimises reflections, keeping you focused whether you're in a bright studio or a dim workspace. These advanced features allow you to fully showcase your creativity and skills.

Designed for productivity, the HB3201 features a 150mm height-adjustable stand, USB-C docking, and a built-in KVM switch, giving you a clean, connected setup ready for effortless multitasking.



See more, adjust less

IPS Black 2.0 technology enhances contrast, deepens blacks, and delivers consistent colours across a broad viewing area. You'll catch more detail in shadowed regions and reduce the need for corrections, giving you full confidence during creative work.



Pantone Validated for reliable colour accuracy

ProGraphic monitors are **Pantone Validated** to ensure precise reproduction of Pantone Matching System colours widely used in design and print. This streamlines your workflow, minimizes revisions, and gives professionals across colour-critical fields the confidence to trust every hue.



Precision colour across every medium

With 99% coverage of the DCI-P3 colour space, ProGraphic monitors provide the accuracy needed for any visual project. Whether it's digital content, print, or film, your work looks exactly how you intended so your audience sees what you see.



Enhanced contrast for sharper decisions

A 3000:1 contrast ratio allows ProGraphic monitors to expose subtle shadows and delicate tonal transitions. This means you see more of your image upfront, making editing and grading decisions easier and more accurate. No detail gets overlooked.

SPECIFIKÁCIÓ

01 KIJELZŐ JELLEMZŐI

Design	4-side edge-to-edge
Átló	31.5", 80cm
Panel	IPS Black 2.0, matte finish
Natív felbontás	3840 x 2160 @60Hz (8.3 megapixel 4K UHD)
Képarány	16:9
Fényerő	450 cd/m²
Statikus kontraszt	3000:1
Speciális kontraszt	80M:1
Válaszidő (GTG)	4ms
Látótér	horizontális/vertikális: 178°/178°, jobb/bal: 89°/89°, fel/le: 89°/89°
Szín támogatás	1.07B 8bit (DCI-P3 99%, sRGB: 100%)
Horizontális szinkronizálás	30 - 140kHz
Látható terület Sz x M	697.3 x 392.2mm, 27.5 x 15.4"
Pixel magasság	0.182mm
Szín	matt, fekete

02 INTERFÉSZEK / CSATLAKOZÓK / VEZÉRLŐK

Jelbemenet	HDMI x1 (v.2.0) DisplayPort x1 (v.1.2) USB-C x1 (PD 96W)
Jel kimenet	DisplayPort x1 (Daisy Chain MST max. 2560 x 1440)
USB HUB	x4 (3x v.3.2 Gen 1 (5Gbps, 4.5W) 1x Type C (5Gbps, 15W))
USB-C DOCK	x1 (Power delivery 96W, LAN, DP out, (not supported on MAC) USB v.3.2 (Gen 1, 5Gbit))
HDCP	igen
Hangszóró csatlakozó	igen
RJ45 (LAN)	x1

03 JELLEMZŐK

KVM switch	igen
Kéfény csökkentés	igen
Villogásmentes	igen
Extra	Delta E <2.0, EyeComfort, Low Blue Light Panel, Eyesafe® Certified, Pantone ValidatedTM, AGLR Polarizer (anti-glare low reflective)
HDR	HDR400
OSD nyelvek	EN, DE, FR, ES, IT, RU, JP, CZ, NL, PL, UA
Vezérlőgombok	Joystick/Power: Up/Input Select, Down/Shortcut, Right/Shortcut, Left/Shortcut

Felhasználói vezérlők	picture adjust (contrast, brightness, uniformity, ACR, Eco, OD, gamma), colour settings (HDR, 6-axis, i-Style colour, colour space, RGB range, colour temp., user preset), PiP/PbP (PiP/PbP, sub source, PiP position, PiP size, swap), OSD (H/ position, V. position, OSD time, OSD background, DDC/CI control, display information), language, recall (recall all), miscellaneous (sharpness, video mode adjust, smart power, USB charge, MST DP-out, USB-C speed, shortcut key, opening logo, power LED, Mac address, FW version), KVM (HDMI, DP, USB-C), input select (input select, DisplayPort mode), audio settings (volume, mute, audio input)
Hangszórók	2 x 2.5W
Kényelem	Kensington-lock™ előkészítve, DDC/CI, DDC2B

04 MECHANIKUS

Kijelző helyzetének beállításai	magasság, forgatható, billenthető, forgatható (forgatás mindkét oldalra)
Magasság beállítása	150mm
Forgatás (PIVOT funkció - portré mód)	90°
Forgó állvány	360°; 180° bal; 180° jobb
Hajlásszög	23° fel; 5° le
VESA állvány	100 x 100mm
Kábelkezelő rendszer	igen

05 TARTOZÉKOKAT TARTALMAZZA

Kábelek	áramellátás (1.8m), USB (1.8m), HDMI (1.8m), DP (1.8m), USB-C (1.0m)
Egyéb	gyors üzembe helyezési útmutató, biztonsági útmutató

06 ENERGIAGAZDÁLKODÁS

Tápegység	belső
Áramellátás	AC 120 - 240V, 50/60Hz
Energiafogyasztás	32W jellemző, 0.5W készenlét, 0.3W kikapcsolva
Áramfogyasztás	0.5W készenlét

07 FENNTARTHATÓSÁG

Előírások	TCO Certified, CE, TÜV-GS, EAC, VCCI-B, PSE, RoHS támogatás, ErP, WEEE, HATÓTÁVOLSÁG, UKCA
Energiahatékonysági osztály ((EU) 2017/1369 rendelet)	F
EPEAT Ezüst	registration varies by country, go to www.epeat.net for details
REACH SVHC	0,1% felett: Vezet

08 MÉRETEK / SÚLY

Termék méretei Sz x H x M	714.5 x 438 (588) x 260mm
----------------------------------	---------------------------



All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects. © IIYAMA CORPORATION. ALL RIGHTS RESERVED