



ProLite X2377HDS - a 23" LED backlit LCD Screen featuring IPS Panel technology which is considered to be the best all around panel type. This IPS panel offers accurate and consistent colour reproduction with wide viewing angles (178°/178°) and great response time (5 ms black-to-black). The ProLite X2377HDS is full HD, has a 5 000,000:1 Advanced Contrast Ratio and 250 cd/m² brightness offering the user clear and vivid images. An array of inputs including HDMI, DVI and VGA connections ensure compatibility across a range of devices including games consoles and work stations. The Prolite X2377HDS has two integrated stereo speakers and is VESA mount compatible. It will provide both excellent performance for photographic, design and web-design and is also an excellent choice for Universities, Corporate and Financial Markets, as well as the rapidly expanding demand for Multi Monitor applications.

01 CARACTERÍSTICAS DE LA PANTALLA

Diagonal	23", 58.4cm
Pantalla	IPS
Resolución nativa	1920 x 1080 (Full HD 1080p, 2.1 megapixel)
Relación de aspecto	16:9
Brillo	250 cd/m ²
Contraste estático	1000:1
Contraste avanzado	5M:1
Tiempo de respuesta (GTG)	5ms
Área de visualización	horizontal/vertical: 178°/178°, derecho/izquierdo: 89°/89°, arriba/abajo: 89°/89°
Soporte de Color	16.7mln
Sincronización horizontal	30 - 80kHz
Área de visualización h x v	509.2 x 286.4mm, 20 x 11.3"
Pixel pitch	0.265mm

02 INTERFACES / CONECTORES / CONTROLADORES

Conector de entrada	VGA x1 DVI x1 HDMI x1
USB HUB	x0

03 CARACTERISTICAS

OSD idioma	EN, DE, FR, ES, IT, PT, CN, RU, JP, CZ, NL, PL
Controles	Power, Menu/ Select, +/- Volume, -/ ECO, Auto/ Exit
Los controles de usuario	picture (brightness, contrast, H. position, V. position, phase, clock, colour temp., auto adjust), OSD (H. position, V. position, OSD time out), display (display mode, i-style Colour, Adv. Contrast, ECO, sharpness, Over Drive), audio (volume, mute, audio input), miscellaneous (language, input select, opening logo, reset), information
Altavoces	2 x 1.5W

04 ASPECTOS MECÁNICOS

Ángulo de inclinación	15° arriba; 5° abajo
Montaje VESA	100 x 100mm

05 ACCESSORIES INCLUDED

Cable	de alimentación
Otro	guía de inicio rápido, guía de seguridad

06 GESTIÓN DE ENERGÍA

Unidad de fuente de alimentación	interno
Fuente de alimentación	AC 100 - 240V, 50/60Hz
Gestión de energía	32W typical, Modo en espera 0,5W, Modo apagado 0,5W

07 SOSTENIBILIDAD

Certificados	TCO Certified, CE, VCCI-B, PSE, RoHS support, ErP, WEEE, REACH
REACH SVHC	por encima de 0.1% de plomo

08 DIMENSIONES / PESO

Producto dimensiones W x H x D	546 x 394.5 x 164mm
Peso (sin caja)	3.4kg

All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects.

© IIYAMA CORPORATION. ALL RIGHTS RESERVED