



ProLite TH6562MTS is a 65" Full HD professional, feature-rich and robust large format display with touch screen functionality. Incorporating the latest MVA panel technology, the display guarantees great viewing from all angles, high brightness and exceptional colour clarity. It also features an ambient light sensor delivering exceptional performance with the added benefit of saving on power. The display supports PIP function. A wide range of video and audio inputs ensures compatibility with multiple platforms. ProLite TH6562MTS is VESA mountable and has a special space at the rear for mounting a small PC or a multimedia player. The OSD can be controlled with both control buttons and an included remote control. This display will suit a massive range of interactive applications including public signage, retail, exhibitions and conference centres, POS/POI, control rooms, and production facilities.

01 CARACTERÍSTICAS DE LA PANTALLA

Diagonal	65", 164cm
Pantalla	MVA CCFL-backlit
Resolución nativa	1920 x 1080 (Full HD 1080p, 2.1 megapixel)
Relación de aspecto	16:9
Contraste avanzado	0M:1
Tiempo de respuesta (GTG)	8ms
Área de visualización	horizontal/vertical: 178°/178°, derecho/izquierdo: 89°/89°, arriba/abajo: 89°/89°
Soporte de Color	1.07B 10bit (8bit + Hi-FRC)
Sincronización horizontal	23 - 92kHz
Área de visualización h x v	1428.48 x 803.52mm, 56.2 x 31.6"
Pixel pitch	0.744mm
Bisel color y acabado	negro, mate

02 INTERFACES / CONECTORES / CONTROLADORES

Conector de entrada analógica	VGA x1 RCA video x1
Conector de entrada digital	DVI x1 HDMI x1
Salida de audio	Altavoces 2 x 12W
USB HUB	x0

03 CARACTERÍSTICAS

Sensor de brillo	si
------------------	----

04 GENERAL

OSD idioma	EN, DE, FR, ES, IT, PT, CN, RU, JP, CZ, NL, PL
------------	--

Los controles de usuario	picture (picture mode, contrast, brightness, color, tint, sharpness, backlight, ACR, colour temperature), sound (volume, mute, audio source, speaker), option (aspect ratio, PIP, video source, auto adjust, clock, phase, H. position, V. position, ambient light sensor, auto detection, touch feature), settings (language, schedule, display wall, power save, monitor ID, image retention, auto adjust, advanced), advanced settings (restore, OSD info box)
--------------------------	---

Plug&Play	DDC2B, Mac OSX
-----------	----------------

05 ASPECTOS MECÁNICOS

Orientación	Horizontal
-------------	------------

Montaje VESA	400 x 400mm
--------------	-------------

06 ACCESSORIES INCLUDED

Cable	de alimentación, USB
-------	----------------------

Guía	guía de inicio rápido, guía de seguridad
------	--

Mando a distancia	sí
-------------------	----

07 GESTIÓN DE ENERGÍA

Unidad de fuente de alimentación	interno
----------------------------------	---------

Fuente de alimentación	AC 100 - 240V, 50/60Hz
------------------------	------------------------

Gestión de energía	550W typical, Modo en espera 0,5W, Modo apagado 0,5W
--------------------	--

08 SOSTENIBILIDAD

Certificados	CB, CE, TÜV-Bauart, RoHS support, ErP, WEEE, REACH
--------------	--

REACH SVHC	por encima de 0.1% de plomo
------------	-----------------------------

09 DIMENSIONES / PESO

Producto dimensiones W x H x D	1522 x 889 x 146mm
--------------------------------	--------------------

Peso (sin caja)	71kg
-----------------	------

All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects.