



ProLite TH6560MTS is a 65" Full HD professional, feature-rich and robust large format display with touch screen functionality. Incorporating the latest MVA panel technology, the display guarantees great viewing from all angles, high brightness and exceptional colour clarity. It also features an ambient light sensor delivering exceptional performance with the added benefit of saving on power. The display supports PIP function. A wide range of video and audio inputs ensures compatibility with multiple platforms. ProLite TH6562MTS is VESA mountable and has a special space at the rear for mounting a small PC or a multimedia player. The OSD can be controlled with both control buttons and an included remote control. This display will suit a massive range of interactive applications including public signage, retail, exhibitions and conference centres, POS/POI, control rooms, and production facilities.

01 DISPLAY CHARACTERISTICS

Diagonal	65", 164cm
Panel	MVA CCFL-backlit
Native resolution	1920 x 1080 (Full HD 1080p, 2.1 megapixel)
Aspect ratio	16:9
Advanced contrast	0M:1
Response time (GTG)	8ms
Viewing zone	horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89°
Colour support	1.07B 10bit (8bit + Hi-FRC)
Horizontal Sync	23 - 92kHz
Viewable area W x H	1428.48 x 803.52mm, 56.2 x 31.6"
Pixel pitch	0.744mm
Bezel colour and finish	black, matte

02 INTERFACES / CONNECTORS / CONTROLS

Analog signal input	VGA x1 RCA Composite x1
Digital signal input	DVI x1 HDMI x1
Audio output	Speakers 2 x 12W
USB HUB	x0

03 FEATURES

Brightness sensor	yes
--------------------------	-----

04 GENERAL

OSD languages	EN, DE, FR, ES, IT, PT, CN, RU, JP, CZ, NL, PL
User controls	picture (picture mode, contrast, brightness, color, tint, sharpness, backlight, ACR, colour temperature), sound (volume, mute, audio source, speaker), option (aspect ratio, PIP, video source, auto adjust, clock, phase, H. position, V. position, ambient light sensor, auto detection, touch feature), settings (language, schedule, display wall, power save, monitor ID, image retention, auto adjust, advanced), advanced settings (restore, OSD info box)
Plug&Play	DDC2B, Mac OSX

05 MECHANICAL

Orientation	landscape
VESA mounting	400 x 400mm

06 ACCESSORIES INCLUDED

Cables	power, USB
Guides	quick start guide, safety guide
Remote control	yes

07 POWER MANAGEMENT

Power supply unit	internal
Power supply	AC 100 - 240V, 50/60Hz
Power usage	550W typical, 0,5W stand by, 0,5W off mode

08 SUSTAINABILITY

Regulations	CB, CE, TÜV-Bauart, RoHS support, ErP, WEEE, REACH
REACH SVHC	above 0.1%: Lead

09 DIMENSIONS / WEIGHT

Product dimensions W x H x D	1522 x 889 x 146mm
Weight (without box)	71kg