



ProLite TH5563MTS is a 55" Full HD professional, feature-rich and robust LED-backlit display with touch functionality. Incorporating the latest Commercial Grade 120Hz IPS panel technology, the display guarantees great viewing from all angles, high brightness and exceptional colour clarity. It also features an ambient light sensor delivering optimal picture quality with the added benefit of saving on power. The display supports PIP, a video-wall function and incorporates a wide range of video and audio inputs which ensures compatibility with multiple platforms. ProLite TH5563MTS is prepared for easy installation using the VESA wall mount. This display will suit a wide range of applications including Interactive Signage, Retail, Exhibitions, Kiosks, Education and Training, Conference Centres and Presentations.

## 01 CARACTERÍSTICAS DE LA PANTALLA

Diagonal	55", 138.5cm
Pantalla	IPS, LED-Backlit
Resolución nativa	1920 x 1080 (Full HD 1080p, 2.1 megapixel)
Relación de aspecto	16:9
Brillo	450 cd/m <sup>2</sup>
Contraste estático	1 300:1
Contraste avanzado	0M:1
Tiempo de respuesta (GTG)	12ms
Área de visualización	horizontal/vertical: 178°/178°, derecho/izquierdo: 89°/89°, arriba/abajo: 89°/89°
Soporte de Color	1.07B 10bit (8bit + Hi-FRC)
Sincronización horizontal	30 - 75kHz
Área de visualización h x v	1209.6 x 680.4mm, 47.6 x 26.8"
Pixel pitch	0.63mm
Bisel color y acabado	negro, mate

## 02 INTERFACES / CONECTORES / CONTROLADORES

<b>Conector de entrada analógica</b>	VGA x1 RCA video x1
<b>Conector de entrada digital</b>	DVI x1 HDMI x1
<b>Salida de audio</b>	Altavoces 2 x 12W
<b>HDCP</b>	si
<b>USB HUB</b>	x0

### 03 CARACTERISTICAS

<b>Sensor de brillo</b>	si
-------------------------	----

### 04 GENERAL

<b>OSD idioma</b>	EN, DE, FR, ES, IT, PT, CN, RU, JP, CZ, NL, PL
-------------------	--

<b>Los controles de usuario</b>	picture (picture mode, contrast, brightness, colour, tint, sharpness, backlight, ACR, colour temp.), sound (volume, mute, audio source, speaker), option (aspect ratio, PIP, video source, auto adjust, clock, phase, H.position, V.position, ambient light sensor, auto detection, touch feature), setting (language, schedule, display wall, power save, set monitor ID, image retention, auto adjust, advanced (restore, OSD info box))
---------------------------------	--

<b>Plug&amp;Play</b>	DDC2B, Mac OSX
----------------------	----------------

### 05 ASPECTOS MECÁNICOS

<b>Orientación</b>	Horizontal
--------------------	------------

<b>Montaje VESA</b>	400 x 200mm
---------------------	-------------

### 06 ACCESSORIES INCLUDED

<b>Cable</b>	de alimentación
--------------	-----------------

<b>Guía</b>	guía de inicio rápido, guía de seguridad
-------------	--

<b>Mando a distancia</b>	sí
--------------------------	----

### 07 GESTIÓN DE ENERGÍA

<b>Unidad de fuente de alimentación</b>	interno
---	---------

<b>Fuente de alimentación</b>	AC 100 - 240V, 50/60Hz
-------------------------------	------------------------

<b>Gestión de energía</b>	142W typical, Modo en espera 0.5W, Modo apagado 0.5W
---------------------------	--

### 08 SOSTENIBILIDAD

<b>Certificados</b>	CB, CE, TÜV-Bauart, RoHS support, ErP, WEEE, REACH
---------------------	--

<b>REACH SVHC</b>	por encima de 0.1% de plomo
-------------------	-----------------------------

### 09 DIMENSIONES / PESO

<b>Producto dimensiones W x H x D</b>	1263 x 744 x 95mm
---------------------------------------	-------------------

<b>Peso (sin caja)</b>	45kg
------------------------	------

