




ProLite TH5563MIS is a 55" Full HD professional, feature-rich and robust LED-backlit display with touch functionality (infrared - 6 compatible touch points). Incorporating the latest Commercial Grade 120Hz IPS panel technology, the display guarantees great viewing from all angles, high brightness and exceptional colour clarity. It also features an ambient light sensor delivering optimal picture quality with the added benefit of saving on power. The display supports PIP, a video-wall function and incorporates a wide range of video and audio inputs which ensures compatibility with multiple platforms. ProLite TH5563MIS is prepared for easy installation using the VESA wall mount. This display will suit a wide range of applications including Interactive Signage, Retail, Exhibitions, Kiosks, Education and Training, Conference Centres and Presentations.



Tecnología táctil - Infrarrojo

La tecnología infrarroja utiliza retroiluminación infrarroja. Un toque se registra con gran precisión cuando la luz infrarroja se bloquea con el dedo o el lápiz. Esta tecnología no se basa en una superposición o sustrato, por lo que es imposible "desgastar" físicamente la pantalla táctil.



IPS

Las pantallas IPS son más conocidas por sus amplios ángulos de visión y sus colores naturales y precisos. Son particularmente adecuados para aplicaciones de color crítico.

01 CARACTERÍSTICAS DE LA PANTALLA

Diagonal	55", 138.5cm
Pantalla	IPS, LED-Backlit
Resolución nativa	1920 x 1080 (Full HD 1080p, 2.1 megapixel)
Relación de aspecto	16:9
Brillo	450 cd/m ²
Contraste estático	1 300:1
Contraste avanzado	0M:1
Tiempo de respuesta (GTG)	12ms
Área de visualización	horizontal/vertical: 178°/178°, derecho/izquierdo: 89°/89°, arriba/abajo: 89°/89°
Soporte de Color	1.07B 10bit (8bit + Hi-FRC)
Sincronización horizontal	30 - 75kHz
Área de visualización h x v	1209.6 x 680.4mm, 47.6 x 26.8"
Pixel pitch	0.63mm
Bisel color y acabado	negro, mate

02 INTERFACES / CONECTORES / CONTROLADORES

Conector de entrada analógica	VGA x1 RCA video x1
Conector de entrada digital	DVI x1 HDMI x1
Salida de audio	Altavoces 2 x 12W
HDCP	si
USB HUB	x0

03 CARACTERÍSTICAS

Sensor de brillo	si
------------------	----

04 GENERAL

OSD idioma	EN, DE, FR, ES, IT, PT, CN, RU, JP, CZ, NL, PL
Los controles de usuario	picture (picture mode, contrast, brightness, colour, tint, sharpness, backlight, ACR, colour temp.), sound (volume, mute, audio source, speaker), option (aspect ratio, PIP, video source, auto adjust, clock, phase, H.position, V.position, ambient light sensor, auto detection, touch feature), setting (language, schedule, display wall, power save, set monitor ID, image retention, auto adjust, advanced (restore, OSD info box))
Plug&Play	DDC2B, Mac OSX

05 ASPECTOS MECÁNICOS

Orientación	Horizontal, vertical
Montaje VESA	400 x 200mm

06 ACCESSORIES INCLUDED

Cable	de alimentación
Guía	guía de inicio rápido, guía de seguridad
Mando a distancia	sí

07 GESTIÓN DE ENERGÍA

Unidad de fuente de alimentación	interno
Fuente de alimentación	AC 100 - 240V, 50/60Hz
Gestión de energía	136W typical, Modo en espera 0.5W, Modo apagado 0.5W

08 SOSTENIBILIDAD

Certificados	CB, CE, TÜV-Bauart, RoHS support, ErP, WEEE, REACH
REACH SVHC	por encima de 0.1% de plomo

09 DIMENSIONES / PESO

Producto dimensiones W x H x D	1273 x 743.5 x 96mm
Peso (sin caja)	45kg

All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects.

© IIYAMA CORPORATION. ALL RIGHTS RESERVED