





































ProLite LH6564S - a 65" Full HD professional large format display

Incorporating AMVA3 panel technology the LH6564S guarantees great viewing from all angles, high brightness and perfect colour clarity. It features an ambient light sensor delivering exceptional performance with the added benefit of saving on power. Features include PIP and PBP perfect for Video Conferencing or handing multi-input content in many environments. Perfect for true impact in Digital Signage.





AMVA3

AMVA3 technology offers higher contrast, darker blacks and much better viewing angles than standard TN technology. The screen will look good no matter what angle you look at it.

PIP

PIP (Picture in Picture) function allows you to watch images coming from two different sources at the same time.

01 DISPLAY CHARACTERISTICS

Diagonal	65", 164cm
Panel	AMVA3 LED, matte finish
Native resolution	1920 x 1080 (Full HD 1080p, 2.1 megapixel)
Aspect ratio	16:9
Panel brightness	450 cd/m ²
Static contrast	4 000:1
Advanced contrast	0M:1
Response time (GTG)	8ms
Viewing zone	horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89°
Colour support	1.07B 10bit (8bit + Hi-FRC)
Horizontal Sync	30 - 83kHz
Viewable area W x H	1428.48 x 803.52mm, 56.2 x 31.6"
Pixel pitch	0.744mm
Bezel colour and finish	black, matte

02

INTERFACES / CONNECTORS / CONTROLS

Analog signal input	VGA x1 RCA Composite x1
Digital signal input	DVI x1 HDMI x1 DisplayPort x1
Audio input	Mini jack x1
Analog signal output	VGA x1
Audio output	RCA (L/R) x1 Speakers 2 x 12W
USB HUB	x0



FEATURES

Max. non-stop operating time	18/7
Housing (bezel)	metal
Brightness sensor	yes



GENERAL

OSD languages	EN, DE, FR, ES, IT, PT, CN, RU, JP, CZ, NL, PL
User controls	picture (picture mode, backlight, contrast, brightness, chroma, phase, sharpness, colour temp., noise reduction, film mode, reset), sound (sound mode, treble, bass, balance, surround, speaker, audio source, reset), screen (PAP setting, display wall, aspect, adjust screen, freeze), setting (language, schedule, power save, control setting, network settings, set monitor ID, HDMI control, advanced, information, reset)
Plug&Play	DDC2B, Mac OSX



Orientation	landscape, portrait
VESA mounting	400 x 400mm

Cables	power, VGA, DVI
Guides	quick start guide, safety guide
Remote control	yes

07 POWER MANAGEMENT


Power supply	DC 1002405060 V
Power usage	250W typical, 0,5W stand by, 0,5W off mode

08 SUSTAINABILITY

Regulations	CB, CE, TÜV-Bauart, RoHS support, ErP, WEEE, CU, REACH
REACH SVHC	above 0.1%: Lead

09 DIMENSIONS / WEIGHT

Product dimensions W x H x D	1511.5 x 881.5 x 90.5mm
Weight (without box)	47.7kg



© IIYAMA CORPORATION. ALL RIGHTS RESERVED