

































70" Interactive LCD Touchscreen with integrated annotation software and USB playback

The TH7067MIS-B1AG is a 70", 10-point touchscreen with integrated interactive EasiNote writing software allowing users to make annotations on files opened directly from a USB device or internal storage. The display supports also playback of presentations, video and almost any other type of content stored on the USB device or internal memory. The high quality commercial ASV LCD screen guarantees great viewing angles from all sides and delivers superb image performance from anywhere in a class or meeting-room. The Anti Glare screen drastically reduces ambient reflection in high brightness environments without compromising sharp clarity of the content. Unlike interactive whiteboards, there are no shadows or reductions in image performance to contend with. The TH7067MIS-B1AG is a perfect solution for educational and corporate use.





The infrared technology uses infrared backlight. A touch event is registered with great accuracy when the infrared light is blocked by finger or stylus. This technology does not rely on an overlay or substrate, so it is impossible to physically "wear out" the touchscreen. Moreover the display characteristics remain virtually unaffected by the touch functionality.



Note

Make notes, sketch, draw, write and share your ideas with your team or students or save them to a cloud drive or USB-stick; collaboration was never easier. Turn your iiyama professional display into a interactive digital whiteboard with Note, our Android-based writing and annotation software.

01 DISPLAY CHARACTERISTICS

Diagonal	69.5", 176.6cm
Panel	ASV LED-Backlit, AG80 Coated Glass
Native resolution	1920 x 1080 (Full HD 1080p, 2.1 megapixel)
Aspect ratio	16:9
Brightness	350 cd/m² with touch
Light transmittance	88%
Static contrast	4 000:1 with touch
Advanced contrast	0M:1
Response time (GTG)	6ms
Viewing zone	horizontal/vertical: 176°/176°, right/left: 88°/88°, up/down: 88°/88°
Colour support	1.07B 10bit
Horizontal Sync	30 - 83kHz
Viewable area W x H	1538.88 x 865.62mm, 60.6 x 34.1"
Pixel pitch	0.802mm
Bezel colour and finish	black, matte

02

TOUCH

Touch technology	infrared
Touch method	stylus, finger
Touch interface	USB
Supported operating systems	All iiyama monitors are Plug & Play and compatible with Windows and Linux. For details regarding the supported OS for the touch models, please refer to the driver instruction file available in the downloads section.



INTERFACES / CONNECTORS / CONTROLS

Analog signal input	VGA x3
Digital signal input	DVI x1 HDMI x3
Audio output	Speakers 2 x 10W
USB HUB	х0



FEATURES

Extra	integrated, interactive annotation tools and applications allowing to browse the Internet, show documents, presentations, video, etc.
Max. non-stop operating time	24/7
Media playback	yes



GENERAL

OSD languages	EN, DE, FR, ES, IT, PT, CN, RU, JP, CZ, NL, PL
User controls	input, brightness, volume (volume, bass, treble, balance, sound mode, mute), zoom (H-position, V-position, phase, clock, aspect ratio, auto), screen (brightness, contrast, sharpness, colour temp.), advanced (Ethernet, display, storage, apps, language & input, date & time, startup and shutdown, floating annotations, about)

Plug&Play DDC2B, Mac OSX



Orientation	landscape, portrait
VESA mounting	400 x 400mm



ACCESSORIES INCLUDED

Cables	power, VGA, USB
Touch pen	x1
Guides	quick start guide, safety guide
Remote control	yes



POWER MANAGEMENT

Power supply unit	internal
Power supply	AC 100 - 240V, 50/60Hz
Power usage	223W typical, 0,5W stand by, 0,5W off mode



SUSTAINABILITY

Regulations	CB, CE, RoHS support, ErP, WEEE, CU, REACH
REACH SVHC	above 0.1%: Lead

10

DIMENSIONS / WEIGHT

Product dimensions W x H x D	1638 x 964.5 x 102.5mm
Weight (without box)	64kg

