




### 34'' IPS ultra-wide screen with a height adjustable stand

ProLite XUB3490WQSU is a 34'' LED monitor featuring the latest IPS Panel technology considered to be the best all round panel type. It offers accurate and consistent colour reproduction with wide viewing angles and a fast response time. UWQHD (Ultra Wide QHD) resolution offers an ultra wide (21:9) viewable area. The large amount of space and good pixel density offered by the size and resolution of this screen provide great potential on the desktop. Very suitable for those who want to use side-by-side applications, watch a movie shot in widescreen format or enrich their gaming experience.



IPS



ULTRA WIDE - UWQHD

IPS displays are best known for wide viewing angles and natural, highly accurate colours. They are especially suited for colour-critical applications.

## 01 DISPLAY CHARACTERISTICS

Diagonal	34", 86.7cm
Panel	AH-IPS, matte finish
Native resolution	3440 x 1440 (4.9 megapixel UWQHD)
Aspect ratio	21:9
Panel brightness	320 cd/m <sup>2</sup>
Static contrast	1000:1
Advanced contrast	80M:1
Response time (GTG)	4ms
Viewing zone	horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89°
Colour support	1.07B 10bit (8bit + Hi-FRC) (sRGB: 109%, NTSC: 77%)
Horizontal Sync	30 - 100kHz
Viewable area W x H	799.8 x 334.8mm, 31.5 x 13.2"
Pixel pitch	0.2325mm
Colour	matte

## 02 INTERFACES / CONNECTORS / CONTROLS

Signal input	HDMI x3 (1xv2.0) DisplayPort x1 (v1.2)
USB HUB	x4 (2xv.2.0 & 2xv.3.0 (charger))
HDCP	yes
Headphone connector	yes

## 03 FEATURES

Blue light reducer	yes
Flicker free	yes
Extra	USB 3.0 battery charger
OSD languages	EN, DE, FR, ES, IT, PT, RU, JP, CZ, NL, PL
Control buttons	Power, Menu, +/- Volume/Mute, -/ ECO/Blue Light Reducer, Input
User controls	picture adjust (contrast, brightness, i-style colour, OD, ACR, ECO), colour adjust (gamma, colour temp.), manual image adjust (video mode adjust, black tuner, memorize setting), PiP/PbP (PiP/PbP, sub win 1/2/3/4 input, PiP size, PiP position, swap), OSD setup (H.position, V. position, OSD timeout, language), extra (reset, auto off, input select, audio input, DisplayPort, opening logo, information), volume, mute
Speakers	2 x 3W
Convenience	Kensington-lock™ prepared, DDC2B, Mac OSX

## 04 MECHANICAL

Display position adjustments	height, swivel, tilt
Height adjustment	130mm
Swivel stand	90°; 45° left; 45° right
Tilt angle	20° up; 4° down
VESA mounting	100 x 100mm

## 05 ACCESSORIES INCLUDED

<b>Cables</b>	power, USB, HDMI, Audio, DP
<b>Other</b>	quick start guide, safety guide

## 06 POWER MANAGEMENT

<b>Power supply unit</b>	internal
<b>Power supply</b>	AC 100 - 240V, 50/60Hz
<b>Power usage</b>	48W typical, 0.5W stand by, 0.5W off mode

## 07 SUSTAINABILITY

<b>Regulations</b>	CE, TÜV-GS, RoHS support, ErP, ENERGY STAR <sup>®</sup> , WEEE, EPEAT, REACH
<b>EPEAT Silver</b>	EPEAT is a comprehensive environmental rating that helps identify greener computers and other electronic equipment. The Silver certification means the monitor meets all required criteria plus at least 50% of the optional requirements. EPEAT Silver is valid in countries where iiyama registers the product. Please visit <a href="http://www.epeat.net">www.epeat.net</a> for the registration status in your country.
<b>REACH SVHC</b>	above 0.1%: Lead

## 08 DIMENSIONS / WEIGHT

<b>Product dimensions W x H x D</b>	827.5 x 404.5 (534.5) x 230mm
<b>Weight (without box)</b>	8.5kg
<b>EAN code</b>	4948570114566

*All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects.*

© IIYAMA CORPORATION. ALL RIGHTS RESERVED