





**55" white open frame touch monitor featuring an eye catching edge-to-edge glass bezel**

With 1920x1080 Full HD resolution and Projective Capacitive 12 point touch technology, the ProLite TF5537MSC-W2AG delivers seamless and accurate touch response. Featuring an IPS Edge LED LCD screen technology, it offers exceptional colour performance and wide viewing angles, making it a perfect display for Interactive Digital Signage. In addition to the superb image quality, the screen comes with a rugged bezel and the panel withstands the 60950-1 ball drop test, making it suitable for demanding environments like table top integration. The open frame ProLite TF5537MSC-W2AG is the ideal solution for Interactive Digital Signage, Instore Retail, Kiosks and Interactive Presentations.



**Touch technology - Capacitive**

This technology uses a sensor-grid of micro-fine wires integrated into the glass that covers the screen. Touch is detected because electrical characteristics of the sensor grid change when human finger is placed on the glass. Thanks to the glass overlay this technology is highly durable, and the touch function remains unaffected even if the glass is scratched. It offers perfect picture performance and will work with human finger (also latex gloved) and stylus-pen.



**Open frame**

Open frame monitors feature special mounting screw holes on all sides of the monitor that can be used for installing the monitor. Open Frame monitors are an ideal solution for kiosk integrators and Instore Retail.

## 01 DISPLAY CHARACTERISTICS

|                                |                                                                       |
|--------------------------------|-----------------------------------------------------------------------|
| <b>Design</b>                  | Open Frame                                                            |
| <b>Diagonal</b>                | 55", 138.8cm                                                          |
| <b>Panel</b>                   | IPS LED, AG coated glass                                              |
| <b>Native resolution</b>       | 1920 x 1080 (2.1 megapixel Full HD)                                   |
| <b>Aspect ratio</b>            | 16:9                                                                  |
| <b>Panel brightness</b>        | 500 cd/m <sup>2</sup>                                                 |
| <b>Brightness</b>              | 420 cd/m <sup>2</sup> with touch                                      |
| <b>Light transmittance</b>     | 84%                                                                   |
| <b>Static contrast</b>         | 1100:1                                                                |
| <b>Response time (GTG)</b>     | 12ms                                                                  |
| <b>Viewing zone</b>            | horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89° |
| <b>Colour support</b>          | 16.7mln                                                               |
| <b>Horizontal Sync</b>         | 31.47 - 67.5kHz                                                       |
| <b>Viewable area W x H</b>     | 1209.6 x 680.4mm, 47.6 x 26.8"                                        |
| <b>Pixel pitch</b>             | 0.4833mm                                                              |
| <b>Bezel colour and finish</b> | white, matte                                                          |

## 02 TOUCH

|                                    |                                                                                                                                                                                                                         |
|------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Touch technology</b>            | projective capacitive                                                                                                                                                                                                   |
| <b>Touch points</b>                | 12 (HID, only with supported OS)                                                                                                                                                                                        |
| <b>Touch method</b>                | stylus, finger, glove (latex)                                                                                                                                                                                           |
| <b>Touch interface</b>             | USB                                                                                                                                                                                                                     |
| <b>Supported operating systems</b> | All iiyama monitors are Plug & Play and compatible with Windows and Linux. For details regarding the supported OS for the touch models, please refer to the driver instruction file available in the downloads section. |

## 03 INTERFACES / CONNECTORS / CONTROLS

|                              |                   |
|------------------------------|-------------------|
| <b>Analog signal input</b>   | VGA x1            |
| <b>Digital signal input</b>  | DVI x1<br>HDMI x1 |
| <b>Audio input</b>           | Mini jack x1      |
| <b>Monitor control input</b> | IR x1             |
| <b>Audio output</b>          | Speakers 2 x 7W   |

## 04 FEATURES

|                                     |             |
|-------------------------------------|-------------|
| <b>Max. non-stop operating time</b> | 24/7        |
| <b>Glass thickness</b>              | 5mm         |
| <b>60950 Ball drop test</b>         | yes         |
| <b>Water and dust protection</b>    | IP1 (front) |
| <b>Housing (bezel)</b>              | metal       |
| <b>OSD key lock</b>                 | yes         |

## 05 GENERAL

|                      |                                |
|----------------------|--------------------------------|
| <b>OSD languages</b> | EN, DE, FR, ES, IT, RU, NL, PL |
|----------------------|--------------------------------|

|                        |                                                                                                                                                                                                                                                                                                                                                                    |
|------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Control buttons</b> | Power, Scroll up/ Volume+, Scroll down/ Volume-, Auto/Exit, Input Select/OK, Menu                                                                                                                                                                                                                                                                                  |
| <b>User controls</b>   | brightness, contrast, colour settings, display adjust (aspect ratio, gamma, sharpness, H. position, V. position, clock, phase, auto adjust) other settings (language, OSD time out, volume, mute, fan, anti image retention, opening logo, factory reset) schedule settings (date and time, timer day set, on timer input select, reset) input source, information |
| <b>Plug&amp;Play</b>   | DDC2B                                                                                                                                                                                                                                                                                                                                                              |

## 06 MECHANICAL

**Orientation** landscape, portrait, face-up

## 07 ACCESSORIES INCLUDED

**Cables** power, VGA, DVI, USB

**Guides** quick start guide, safety guide

**Remote control** yes (batteries included)

## 08 POWER MANAGEMENT

**Power supply unit** internal

**Power supply** AC 100 - 240V, 50/60Hz

**Power usage** 76W typical, 0.5W stand by, 0.5W off mode

## 09 SUSTAINABILITY

**Regulations** CE, TÜV-Bauart, RoHS support, ErP, WEEE, CU, REACH

**REACH SVHC** above 0.1%: Lead

## 10 DIMENSIONS / WEIGHT

**Product dimensions W x H x D** 1294.5 x 765.5 x 67.5mm

**Weight (without box)** 45.7kg

