




**32" white open frame touch monitor built into an eye catching edge-to-edge glass bezel**

With 1920x1080 Full HD resolution and Projective Capacitive 12 point touch technology, the ProLite TF3237MSC-W3AG delivers seamless and accurate touch response. Featuring an AMVA3 Edge LED LCD screen technology, it offers exceptional colour performance and wide viewing angles, making it a perfect display for Interactive Digital Signage. In addition to the superb image quality, the screen comes with a rugged bezel and the panel withstands the 60950-1 ball drop test, making it suitable for demanding environments like table top integration. The open frame ProLite TF3237MSC-W3AG is the ideal solution for Interactive Digital Signage, Instore Retail, Kiosks and Interactive Presentations.



**Touch technology - Capacitive**

This technology uses a sensor-grid of micro-fine wires integrated into the glass that covers the screen. Touch is detected because electrical characteristics of the sensor grid change when human finger is placed on the glass. Thanks to the glass overlay this technology is highly durable, and the touch function remains unaffected even if the glass is scratched. It offers perfect picture performance and will work with human finger (also latex gloved) and stylus-pen.



**Open frame**

Open frame monitors feature special mounting screw holes on all sides of the monitor that can be used for installing the monitor. Open Frame monitors are an ideal solution for kiosk integrators and Instore Retail.

## 01 DISPLAY CHARACTERISTICS

|                         |   |
|-------------------------|---|
| Design                  | Open Frame  |
| Diagonal                | 31.5", 80cm   |
| Panel                   | AMVA3 LED, AG coated glass  |
| Native resolution       | 1920 x 1080 (2.1 megapixel Full HD)                                   |
| Aspect ratio            | 16:9  |
| Brightness              | 500 cd/m <sup>2</sup> typical   |
| Brightness              | 420 cd/m <sup>2</sup> with touch                                      |
| Static contrast         | 3 000:1 typical   |
| Light transmittance     | 84%   |
| Response time           | 8ms   |
| Viewing zone            | horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89° |
| Colour support          | 16.7mIn 8bit (6bit + Hi-FRC)  |
| Horizontal Sync         | 31.47 - 67.5KHz   |
| Vertical Sync           | 47 - 63Hz   |
| Viewable area W x H     | 698.4 x 392.8mm, 27.5 x 15.5"   |
| Pixel pitch             | 0.364mm   |
| Bezel colour and finish | white, matte  |

## 02 TOUCH

|                             |   |
|-----------------------------|---|
| Touch technology            | projective capacitive   |
| Touch points                | 12 (HID, only with supported OS)  |
| Touch method                | stylus, finger, glove (latex)   |
| Touch interface             | USB, RS-232c  |
| Supported operating systems | All iiyama monitors are Plug & Play and compatible with Windows and Linux. For details regarding the supported OS for the touch models, please refer to the driver instruction file available in the downloads section. |

## 03 INTERFACES / CONNECTORS / CONTROLS

|                       |                   |
|-----------------------|-------------------|
| Analog signal input   | VGA x1            |
| Digital signal input  | DVI x1<br>HDMI x1 |
| Audio input           | Mini jack x1      |
| Monitor control input | IR x1             |
| Audio output          | Speakers 2 x 7W   |

## 04 FEATURES

|                              |             |
|------------------------------|-------------|
| Max. non-stop operating time | 24/7        |
| Glass thickness              | 4mm         |
| 60950 Ball drop test         | yes         |
| Water and dust protection    | IP1 (front) |
| Housing (bezel)              | metal       |
| OSD key lock                 | yes         |

## 05 GENERAL

|                 |  |
|-----------------|--|
| OSD languages   | EN, DE, FR, ES, IT, RU, NL, PL   |
| Control buttons | Power, Scroll up/ Volume+, Scroll down/ Volume-, Auto/Exit, Input Select/OK, Menu  |
| User controls   | brightness, contrast, colour settings, display adjust (aspect ratio, gamma, sharpness, H. position, V. position, clock, phase, auto adjust) other settings (language, OSD time out, volume, mute, fan, anti image retention, opening logo, factory reset) schedule settings (date and time, timer day set, on timer input select, reset) input source, information |
| Plug&Play       | DDC2B  |

## 06 MECHANICAL

|               |                              |
|---------------|------------------------------|
| Orientation   | landscape, portrait, face-up |
| VESA mounting | 400 x 200mm                  |

## 07 ACCESSORIES INCLUDED

|                |                                 |
|----------------|---------------------------------|
| Cables         | power, VGA, DVI, USB            |
| Guides         | quick start guide, safety guide |
| Remote control | yes (batteries included)        |

## 08 POWER MANAGEMENT


|                   |   |
|-------------------|---|
| Power supply unit | internal                                  |
| Power supply      | AC 100 - 240V, 50/60Hz                    |
| Power usage       | 48W typical, 0.5W stand by, 0.5W off mode |

## 09 SUSTAINABILITY

|                         |                             |
|-------------------------|-----------------------------|
| Regulations             | CE, TÜV-Bauart, CU          |
| Energy efficiency class | B                           |
| Other                   | REACH SVHC above 0.1%: Lead |

## 10 DIMENSIONS / WEIGHT

|                              |                    |
|------------------------------|--------------------|
| Product dimensions W x H x D | 781.5 x 476 x 69mm |
| Weight (without box)         | 17.3kg             |
| EAN code                     | 4948570114993      |



## 11 EU ENERGY EFFICIENCY LABEL

|                           |                            |
|---------------------------|----------------------------|
| Manufacturer              | iiyama                     |
| Model                     | ProLite TF3237MSC-W3AG     |
| Energy efficiency class   | B                          |
| Visible screen diagonal   | 80cm; 31.5"; (32" segment) |
| ON mode power consumption | 54.2W                      |
| Annual energy consumption | 79kWh/annum*               |
| Power in Standby          | 0.5W stand by              |
| Resolution                | 1920 x 1080                |

*This is information under Regulation (EU) No 1062/2010.\*Based on the power consumption of the television operating 4 hours per day for 365 days. The actual energy consumption will depend on how the television is used.*

*All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects.*

© IYAMA CORPORATION. ALL RIGHTS RESERVED