



27" WQHD monitor that answers your need for extra workspace

Do you spend most of your workday juggling between multiple applications and windows and there is simply never enough of space on the screen? If the answer is yes – you’ve come to the right place. The 27" WQHD X2788QS can easily accommodate almost 77% more information on the screen than a Full HD display. Problem solved. In addition, the IPS technology panel offers accurate and consistent colour reproduction with wide viewing angles and high contrast and brightness values guaranteeing the monitor will provide excellent performance for photographic and web design. Let your creativity loose, iiyama X2788QS will not let you down. Buy it at an iiyama Authorized Reseller to enjoy our 3-year on-site-swap warranty. If you need a monitor with a height adjustable stand, check out [ProLite XB2788QS-B1](#).



IPS Technology

IPS technology offers higher contrast, darker blacks and much better viewing angles than standard TN technology. The screen will look good no matter from what angle you look at it.



WQHD

With true WQHD 2560 x 1440p resolution your monitor is ready to display high definition images. This means you can accommodate more information on your screen, i.e. over 76% more in comparison to a 1920 x 1080 monitor.

01 DISPLAY CHARACTERISTICS

Diagonal	27", 68.5cm
Panel	IPS Panel Technology LED, matte finish
Native resolution	2560 x 1440 (3.7 megapixel WQHD)
Aspect ratio	16:9
Brightness	350 cd/m ² typical
Static contrast	1 000:1 typical
Advanced contrast	5M:1
Response time	5ms
Viewing zone	horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89°
Colour support	16.7mIn 8bit (6bit + Hi-FRC)
Horizontal Sync	30 - 100KHz
Vertical Sync	55 - 75Hz
Viewable area W x H	596.7 x 335.7mm, 23.5 x 13.2"
Pixel pitch	0.233mm
Colour	matte, black

02 INTERFACES / CONNECTORS / CONTROLS

Signal input	DVI x1 HDMI x1 DisplayPort x1
HDCP	yes

03 FEATURES

Blue light reducer	yes
Flicker free	yes
FreeSync support	HDMI&DisplayPort: 2560x1440@60Hz
OSD languages	EN, DE, FR, IT, CN, RU, JP, CZ, NL, PL
Control buttons	Power, Input/ Select / Blue light reducer, Scroll up/ Volume, Scroll down/ i-Style Colour, Menu
User controls	input, picture (brightness, contrast, sharpness, OD, ACR, ECO, blue light reducer), audio (volume, mute, audio input), colour settings, language, OSD settings (OSD H. position, OSD V. position, OSD background, OSD time out), setup menu (video mode adjust, FreeSync-DP, FreeSync-HDMI, opening logo, LED, information, reset)
Speakers	2 x 2.5W
Convenience	Kensington-lock™ prepared, DDC2B, Mac OSX

04 MECHANICAL

Display position adjustments	tilt
Tilt angle	20° up; 3° down
VESA mounting	100 x 100mm

05 ACCESSORIES INCLUDED

Cables	power, HDMI, DP
Other	quick start guide, safety guide

06 POWER MANAGEMENT

Power supply unit	internal
Power supply	AC 100 - 240V, 50/60Hz
Power usage	41W typical, 0.5W stand by

07 SUSTAINABILITY

Regulations	CE, TÜV-Bauart, VCCI-B, PSE, CU
Energy efficiency class	C
Other	REACH SVHC above 0.1%: Lead

08 DIMENSIONS / WEIGHT

Product dimensions W x H x D	643.5 x 462 x 242mm
Weight (without box)	4.4kg
EAN code	4948570115259

09 EU ENERGY EFFICIENCY LABEL

Manufacturer	iiyama
Model	ProLite X2788QS-B1
Energy efficiency class	C
Visible screen diagonal	68cm; 27"; (27" segment)
ON mode power consumption	47.2W
Annual energy consumption	69kWh/annum*
Power in Standby	0.5W stand by
Resolution	2560 x 1440

*This is information under Regulation (EU) No 1062/2010.*Based on the power consumption of the television operating 4 hours per day for 365 days. The actual energy consumption will depend on how the television is used.*

All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects.

© IIYAMA CORPORATION. ALL RIGHTS RESERVED