




### 24'' monitor with an integrated web camera and microphone

The XB2472HSUC is a high-end desktop monitor for demanding users looking for a high quality screen assuring seamless compatibility with any video or web conferencing software. The VA matrix offers wide viewing angles and sharp contrast. The blue light reducer function with flicker free LCD technology reduces eye strain and offers a more comfortable viewing experience. Supplied with a height-adjustable stand featuring swivel and pivot functions, allows you to adjust the position of the screen to your preferences. Furthermore, the versatile connectivity options assure cross platform compatibility (VGA, DVI, DisplayPort and USB hub) and make the XB2472HSUC the right panel to choose for your connected workplace.



#### Webcam & Microphone

The web camera and microphone guarantee seamless compatibility with any video or web conferencing platforms.



#### HAS + Pivot

With a height adjustable stand you will create an ergonomic work posture and position that meets all health and safety requirements. This will not only prevent any health issues but will also increase your productivity. The pivot function allows the screen to rotate from landscape to portrait orientation. This functionality can be useful if the application requires more height than width.

## 01 DISPLAY CHARACTERISTICS

|                     |   |
|---------------------|---|
| Diagonal            | 23.6", 59.8cm   |
| Panel               | VA LED, matte finish  |
| Native resolution   | 1920 x 1080 (2.1 megapixel Full HD)                                   |
| Aspect ratio        | 16:9  |
| Panel brightness    | 250 cd/m <sup>2</sup>   |
| Static contrast     | 3 000:1   |
| Advanced contrast   | 12M:1   |
| Response time (GTG) | 6ms   |
| Viewing zone        | horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89° |
| Colour support      | 16.7mIn (sRGB: 99%; NTSC: 72%)  |
| Horizontal Sync     | 30 - 94kHz  |
| Viewable area W x H | 521.28 x 293.2mm, 20.5 x 11.5"  |
| Pixel pitch         | 0.2715mm  |
| Colour              | matte   |

## 02 INTERFACES / CONNECTORS / CONTROLS

|                     |                                    |
|---------------------|------------------------------------|
| Signal input        | VGA x1<br>DVI x1<br>DisplayPort x1 |
| USB HUB             | x2 (v.2.0)                         |
| HDCP                | yes                                |
| Headphone connector | yes                                |

## 03 FEATURES

|                    |   |
|--------------------|---|
| Blue light reducer | yes   |
| Flicker free       | yes   |
| Extra              | integrated webcam (2.0 megapixel) and microphone  |
| OSD languages      | EN, DE, FR, ES, IT, RU, CZ, NL, PL  |
| Control buttons    | Power, Menu, Scroll up/ Volume, Scroll down/ ECO, Input/ Select   |
| User controls      | picture (brightness, contrast, H. position, V. position, phase, clock, colour temp., auto adjust), OSD (H. position, V. position, timeout, transparency), display (display mode, i-Style Colour, ACR, X-Res Technology, sharpness, OD, gamma, blue light reducer), audio settings (volume, mute, audio input), miscellaneous (language, input select, opening logo, after AC cut, ECO mode, reset), information |
| Speakers           | 2 x 2W  |
| Convenience        | Kensington-lock™ prepared, DDC2B, Mac OSX   |

## 04 MECHANICAL

|                              |  |
|------------------------------|--|
| Display position adjustments | height, pivot (rotation), swivel, tilt |
| Height adjustment            | 130mm                                  |
| Rotation (PIVOT function)    | 90°                                    |
| Swivel stand                 | 180°; 90° left; 90° right              |
| Tilt angle                   | 22° up; 5° down                        |
| VESA mounting                | 100 x 100mm                            |

## 05 ACCESSORIES INCLUDED

|               |                                 |
|---------------|---------------------------------|
| <b>Cables</b> | power, USB, DP                  |
| <b>Other</b>  | quick start guide, safety guide |

## 06 POWER MANAGEMENT

|                          |   |
|--------------------------|---|
| <b>Power supply unit</b> | internal                                    |
| <b>Power supply</b>      | AC 100 - 240V, 50/60Hz                      |
| <b>Power usage</b>       | 21.5W typical, 0.5W stand by, 0.5W off mode |

## 07 SUSTAINABILITY

|                     |  |
|---------------------|--|
| <b>Regulations</b>  | CE, TÜV-Bauart, RoHS support, ErP, ENERGY STAR <sup>®</sup> , WEEE, EPEAT, REACH   |
| <b>EPEAT Silver</b> | EPEAT is a comprehensive environmental rating that helps identify greener computers and other electronic equipment. The Silver certification means the monitor meets all required criteria plus at least 50% of the optional requirements. EPEAT Silver is valid in countries where iiyama registers the product. Please visit <a href="http://www.epeat.net">www.epeat.net</a> for the registration status in your country. |
| <b>REACH SVHC</b>   | above 0.1%: Lead   |

## 08 DIMENSIONS / WEIGHT

|                                     |                             |
|-------------------------------------|-----------------------------|
| <b>Product dimensions W x H x D</b> | 557 x 406.5 (536.5) x 230mm |
| <b>Weight (without box)</b>         | 5.8kg                       |
| <b>EAN code</b>                     | 4948570115327               |

*All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects.*

© IIYAMA CORPORATION. ALL RIGHTS RESERVED