




24" monitor with an integrated web camera and microphone

The XB2472HSUC is a high-end desktop monitor for demanding users looking for a high quality screen assuring seamless compatibility with any video or web conferencing software. The VA matrix offers wide viewing angles and sharp contrast. The blue light reducer function with flicker free LCD technology reduces eye strain and offers a more comfortable viewing experience. Supplied with a height-adjustable stand featuring swivel and pivot functions, allows you to adjust the position of the screen to your preferences. Furthermore, the versatile connectivity options assure cross platform compatibility (VGA, DVI, DisplayPort and USB hub) and make the XB2472HSUC the right panel to choose for your connected workplace.



Webcam & Microphone

The web camera and microphone guarantee seamless compatibility with any video or web conferencing platforms.



HAS + Pivot

With a height adjustable stand you will create an ergonomic work posture and position that meets all health and safety requirements. This will not only prevent any health issues but will also increase your productivity. The pivot function allows the screen to rotate from landscape to portrait orientation. This functionality can be useful if the application requires more height than width.

01 DISPLAY CHARACTERISTICS

Diagonal	23.6", 59.8cm
Panel	VA LED, matte finish
Native resolution	1920 x 1080 (2.1 megapixel Full HD)
Aspect ratio	16:9
Panel brightness	250 cd/m ²
Static contrast	3 000:1
Advanced contrast	12M:1
Response time (GTG)	6ms
Viewing zone	horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89°
Colour support	16.7mIn (sRGB: 99%; NTSC: 72%)
Horizontal Sync	30 - 94kHz
Viewable area W x H	521.28 x 293.2mm, 20.5 x 11.5"
Pixel pitch	0.2715mm
Colour	matte

02 INTERFACES / CONNECTORS / CONTROLS

Signal input	VGA x1 DVI x1 DisplayPort x1
USB HUB	x2 (v.2.0)
HDCP	yes
Headphone connector	yes

03 FEATURES

Blue light reducer	yes
Flicker free	yes
Extra	integrated webcam (2.0 megapixel) and microphone
OSD languages	EN, DE, FR, ES, IT, RU, CZ, NL, PL
Control buttons	Power, Menu, Scroll up/ Volume, Scroll down/ ECO, Input/ Select
User controls	picture (brightness, contrast, H. position, V. position, phase, clock, colour temp., auto adjust), OSD (H. position, V. position, timeout, transparency), display (display mode, i-Style Colour, ACR, X-Res Technology, sharpness, OD, gamma, blue light reducer), audio settings (volume, mute, audio input), miscellaneous (language, input select, opening logo, after AC cut, ECO mode, reset), information
Speakers	2 x 2W
Convenience	Kensington-lock™ prepared, DDC2B, Mac OSX

04 MECHANICAL

Display position adjustments	height, pivot (rotation), swivel, tilt
Height adjustment	130mm
Rotation (PIVOT function)	90°
Swivel stand	180°; 90° left; 90° right
Tilt angle	22° up; 5° down
VESA mounting	100 x 100mm

05 ACCESSORIES INCLUDED

Cables	power, USB, DP
Other	quick start guide, safety guide

06 POWER MANAGEMENT

Power supply unit	internal
Power supply	AC 100 - 240V, 50/60Hz
Power usage	21.5W typical, 0.5W stand by, 0.5W off mode

07 SUSTAINABILITY

Regulations	CE, TÜV-Bauart, RoHS support, ErP, ENERGY STAR [®] , WEEE, EPEAT, REACH
EPEAT Silver	EPEAT is a comprehensive environmental rating that helps identify greener computers and other electronic equipment. The Silver certification means the monitor meets all required criteria plus at least 50% of the optional requirements. EPEAT Silver is valid in countries where iiyama registers the product. Please visit www.epeat.net for the registration status in your country.
REACH SVHC	above 0.1%: Lead

08 DIMENSIONS / WEIGHT

Product dimensions W x H x D	557 x 406.5 (536.5) x 230mm
Weight (without box)	5.8kg
EAN code	4948570115327

All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects.

© IIYAMA CORPORATION. ALL RIGHTS RESERVED