



### Stylish 32" VA panel with 4K resolution

The ProLite X3272UHS is a 32" 4K monitor capable of displaying 4 times more information than a Full HD screen. It will hence suit a massive range of applications requiring an above average viewable area, like desktop publishing, CAD/CAM drawing, data virtualization, photographic and web design. The VA panel technology offers exceptional colour performance, high contrast and wide viewing angles. HDMI, DisplayPort, integrated speakers and a headphone socket ensure compatibility across various devices and media platforms.



**4K**

UHD resolution (3840x2160), better known as 4K, offers a gigantic viewable area with 4 times more information and work space than a Full HD screen. Due to the high DPI (dots per inch), it displays an incredibly sharp and crisp image.



**VA matrix**

VA panel technology offers higher contrast, darker blacks and much better viewing angles than standard TN technology. The screen will look good no matter what angle you look at it.

## 01 DISPLAY CHARACTERISTICS

Diagonal	31.5", 80cm
Panel	VA LED, matte finish
Native resolution	3840 x 2160 @60Hz (HDMI&DisplayPort, 8.3 megapixel 4K UHD)
Aspect ratio	16:9
Brightness	300 cd/m <sup>2</sup> typical
Static contrast	3000:1 typical
Advanced contrast	50M:1
Response time	3ms
Viewing zone	horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89°
Colour support	1.07B 10bit (8bit + Hi-FRC) (sRGB: 137%, NTSC: 97%)
Horizontal Sync	30 - 135KHz
Vertical Sync	24 - 75Hz
Viewable area W x H	695.04 x 390.96mm, 27.4 x 15.4"
Pixel pitch	0.181mm
Colour	matte, black

## 02 INTERFACES / CONNECTORS / CONTROLS

Signal input	HDMI x2 DisplayPort x1
HDCP	yes
Headphone connector	yes

## 03 FEATURES

Blue light reducer	yes
Flicker free	yes
Extra	PiP
OSD languages	EN, DE, FR, ES, IT, PT, RU, JP, CZ, NL, PL
Control buttons	Power/ Menu, Scroll up, Scroll down/ ECO Mode, Left/ Input Select, Right/ Audio Adjust
User controls	luminance (contrast, brightness, i-Style Colour, ACR, OverDrive), image setup (aspect ratio), colour temperature, OSD setup (H. position, V. position, timeout, language), PIP (PIP setting, size, position, swap), extra (input select, DDC/CI, reset, information)
Speakers	2 x 2W
Convenience	Kensington-lock™ prepared, DDC/CI, DDC2B, Mac OSX

## 04 MECHANICAL

Display position adjustments	tilt
Tilt angle	12° up; 4° down
VESA mounting	100 x 100mm

## 05 ACCESSORIES INCLUDED

Cables	power, HDMI, DP
Other	quick start guide, safety guide

## 06 POWER MANAGEMENT

Power supply unit	internal
Power supply	AC 100 - 240V, 50/60Hz
Power usage	52W typical, 0.5W stand by

## 07 SUSTAINABILITY

Regulations	CE, TÜV-Bauart, VCCI-B, PSE, CU
Energy efficiency class	B
Other	REACH SVHC above 0.1%: Lead

## 08 DIMENSIONS / WEIGHT

Product dimensions W x H x D	729.5 x 546 x 254mm
Weight (without box)	6.8kg
EAN code	4948570115754

## 09 EU ENERGY EFFICIENCY LABEL

Manufacturer	iiyama
Model	ProLite X3272UHS-B1
Energy efficiency class	B
Visible screen diagonal	80cm; 31.5"; (32" segment)
ON mode power consumption	52W
Annual energy consumption	76kWh/annum*
Power in Standby	0.5W stand by
Resolution	3840 x 2160

*This is information under Regulation (EU) No 1062/2010.\*Based on the power consumption of the television operating 4 hours per day for 365 days. The actual energy consumption will depend on how the television is used.*

*All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects.*

© IIYAMA CORPORATION. ALL RIGHTS RESERVED