




Stylish 32" VA panel with 4K resolution

The ProLite X3272UHS is a 32" 4K monitor capable of displaying 4 times more information than a Full HD screen. It will hence suit a massive range of applications requiring an above average viewable area, like desktop publishing, CAD/CAM drawing, data virtualization, photographic and web design. The VA panel technology offers exceptional colour performance, high contrast and wide viewing angles. HDMI, DisplayPort, integrated speakers and a headphone socket ensure compatibility across various devices and media platforms.



4K

UHD resolution (3840x2160), better known as 4K, offers a gigantic viewable area with 4 times more information and work space than a Full HD screen. Due to the high DPI (dots per inch), it displays an incredibly sharp and crisp image.



VA

VA panel technology offers higher contrast, darker blacks and much better viewing angles than standard TN technology. The screen will look good no matter what angle you look at it.

01 DISPLAY CHARACTERISTICS

Diagonal	31.5", 80cm
Panel	VA LED, matte finish
Native resolution	3840 x 2160 @60Hz (HDMI&DisplayPort, 8.3 megapixel 4K UHD)
Aspect ratio	16:9
Panel brightness	300 cd/m ²
Static contrast	3000:1
Advanced contrast	50M:1
Response time (GTG)	3ms
Viewing zone	horizontal/vertical: horizontal°/vertical horizontal°, right/left: 0°/0°, up/down: 0°/0°
Colour support	1.07B 10bit (8bit + Hi-FRC) (sRGB: 137%, NTSC: 97%)
Horizontal Sync	30 - 135kHz
Viewable area W x H	695.04 x 390.96mm, 27.4 x 15.4"
Pixel pitch	0.181mm
Colour	matte

02 INTERFACES / CONNECTORS / CONTROLS

Signal input	HDMI x2 DisplayPort x1
HDCP	yes
Headphone connector	yes

03 FEATURES

Blue light reducer	yes
Flicker free	yes
Extra	PiP
OSD languages	EN, DE, FR, ES, IT, PT, RU, JP, CZ, NL, PL
Control buttons	Power/ Menu, Scroll up, Scroll down/ ECO Mode, Left/ Input Select, Right/ Audio Adjust
User controls	luminance (contrast, brightness, i-Style Colour, ACR, OverDrive), image setup (aspect ratio), colour temperature, OSD setup (H. position, V. position, timeout, language), PIP (PIP setting, size, position, swap), extra (input select, DDC/CI, reset, information)
Speakers	2 x 2W
Convenience	Kensington-lock™ prepared, DDC/CI, DDC2B, Mac OSX

04 MECHANICAL

Display position adjustments	tilt
Tilt angle	12° up; 4° down
VESA mounting	100 x 100mm

05 ACCESSORIES INCLUDED

Cables	power, HDMI, DP
Other	quick start guide, safety guide

06 POWER MANAGEMENT

Power supply unit

internal

Power supply

AC AC - AC V, AC /V, 100Hz

Power usage

52W typical, 0.5W stand by, 0.5W off mode

07 SUSTAINABILITY

Regulations

CE, TÜV-Bauart, VCCI-B, PSE, RoHS support, ErP, WEEE, CU, REACH

REACH SVHC

above 0.1%: Lead

08 DIMENSIONS / WEIGHT

Product dimensions W x H x D

729.5 x 546 x 254mm

Weight (without box)

6.8kg

EAN code

4948570115754

© IIYAMA CORPORATION. ALL RIGHTS RESERVED