



### 27" IPS panel with 5K resolution and edge-to-edge glass finish

If you consider yourself a demanding user who settles only for the best specifications and classy design, this screen is for you. Featuring 5K (5120x2880) resolution, the XB2779QQS can display 14,7 MegaPixels on the screen – a stunning 7 times more than a Full HD monitor. Users can create their own workspace by displaying and manipulating multiple applications at the same time. The IPS matrix guarantees high performance with accurate and consistent colour reproduction and wide viewing angles. The XB2779QQS is perfect for graphic and web design.



**5K**

5K (5120x2880) resolution means a monitor can display 14.7 MegaPixels on the screen – a stunning 7 times more than a Full HD monitor.



**IPS**

IPS technology offers higher contrast, darker blacks and much better viewing angles than standard TN technology. The screen will look good no matter what angle you look at it.

## 01 DISPLAY CHARACTERISTICS

Diagonal	27", 68.3cm
Panel	IPS LED
Native resolution	5120 x 2880 @60Hz (14.7 megapixel 5K, DisplayPort)
Aspect ratio	16:9
Brightness	440 cd/m <sup>2</sup> typical
Static contrast	1 200:1 typical
Advanced contrast	80M:1
Response time	4ms
Viewing zone	horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89°
Colour support	16.7mIn 8bit (6bit + Hi-FRC) (sRGB: 99%; NTSC: 72%)
Horizontal Sync	30 - 180KHz
Vertical Sync	55 - 75Hz
Viewable area W x H	595.2 x 334.8mm, 23.4 x 13.2"
Pixel pitch	0.116mm
Colour	black, silver

## 02 INTERFACES / CONNECTORS / CONTROLS

Signal input	HDMI x3 (max. 3840x2160 @60Hz) DisplayPort x2 (v.1.4 max. 5120 x 2880 @60Hz)
HDCP	yes
Headphone connector	yes

## 03 FEATURES

Blue light reducer	yes
Flicker free	yes
Extra	PiP, PbP, 5K resolution is only available via the DisplayPort input and requires a graphic card with DisplayPort 1.4 support (MST not supported)
OSD languages	EN, DE, FR, IT, CN, RU, JP, CZ, NL, PL
Control buttons	Power, Input/ Select, Scroll up/ Audio, Scroll down/ i-Style Colour, Menu/Exit
User controls	input, picture (picture format, brightness, contrast, sharpness, OD, ACR, ECO, X-Res Technology), PiP/PbP (PiP/PbP mode, sub win input, PiP size, PiP position, swap), audio (volume, mute, audio input), colour (warm, normal, cool, user colour, i-Style colour, blue light reducer), language, OSD settings (OSD H. position, OSD V. position, OSD background, OSD time out), setup menu (DP format, opening logo, LED, auto pow. off, information, reset)
Speakers	2 x 2.5W

## 04 MECHANICAL

Display position adjustments	height, swivel, tilt
Height adjustment	130mm
Swivel stand	90°; 45° left; 45° right
Tilt angle	17° up; 2° down
VESA mounting	100 x 100mm

## 05 ACCESSORIES INCLUDED

Cables	power, HDMI, DP
--------	-----------------

Other	quick start guide, safety guide
-------	---------------------------------

## 06 POWER MANAGEMENT

Power supply unit	internal
Power supply	AC 100 - 240V, 50/60Hz
Power usage	60W typical, 0.5W stand by

## 07 SUSTAINABILITY

Regulations	CE, TÜV-Bauart, VCCI-B, PSE, Energy Star , CU
Energy efficiency class	D
Other	REACH SVHC above 0.1%: Lead

## 08 DIMENSIONS / WEIGHT

Product dimensions W x H x D	650 x 434.5 (564.5) x 230mm
Weight (without box)	8.2kg
EAN code	4948570115525

## 09 EU ENERGY EFFICIENCY LABEL

Manufacturer	iiyama
Model	ProLite XB2779QQS-S1
Energy efficiency class	D
Visible screen diagonal	68cm; 26.9"; (27" segment)
ON mode power consumption	64.4W
Annual energy consumption	94kWh/annum*
Power in Standby	0.5W stand by
Resolution	5120 x 2880

*This is information under Regulation (EU) No 1062/2010.\*Based on the power consumption of the television operating 4 hours per day for 365 days. The actual energy consumption will depend on how the television is used.*

*All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects.*

© IIYAMA CORPORATION. ALL RIGHTS RESERVED