




24" Full HD monitor with VA panel and a height adjustable stand

ProLite XB2474HS - a 24" LED backlit LCD Screen featuring VA panel technology, guarantees accurate and consistent colour reproduction with wide viewing angles. Triple input configuration (VGA, HDMI, DisplayPort) assures compatibility with many platforms. The monitor features a height adjustable stand with PIVOT function making it an excellent choice for Universities, Corporate and Financial Markets.



VA

VA panel technology offers higher contrast, darker blacks and much better viewing angles than standard TN technology. The screen will look good no matter what angle you look at it.



HAS + Pivot

With a height adjustable stand you will create an ergonomic work posture and position that meets all health and safety requirements. This will not only prevent any health issues but will also increase your productivity. The pivot function allows the screen to rotate from landscape to portrait orientation. This functionality can be useful if the application requires more height than width.

01 DISPLAY CHARACTERISTICS

Diagonal	23.6", 60cm
Panel	VA LED, matte finish
Native resolution	1920 x 1080 @75Hz (HDMI&DisplayPort, 2.1 megapixel Full HD)
Aspect ratio	16:9
Panel brightness	250 cd/m ²
Static contrast	3000:1
Advanced contrast	12M:1
Response time (GTG)	4ms
Viewing zone	horizontal/vertical: horizontal°/vertical horizontal°, right/left: 0°/0°, up/down: 0°/0°
Colour support	16.7mIn (sRGB: 99%; NTSC: 72%)
Horizontal Sync	30 - 80kHz
Viewable area W x H	521.3 x 293.2mm, 20.5 x 11.5"
Pixel pitch	0.272mm
Colour	matte

02 INTERFACES / CONNECTORS / CONTROLS

Signal input	VGA x1 HDMI x1 DisplayPort x1
HDCP	yes
Headphone connector	yes

03 FEATURES

Blue light reducer	yes
Flicker free	yes
OSD languages	EN, DE, FR, IT, CN, RU, JP, CZ, NL, PL
Control buttons	Power, Input Select/ Select, Scroll up/ Audio, Scroll down/ i-Style Colour, Menu/ Exit
User controls	auto adjust, picture adjust (contrast, brightness, ACR, ECO, OD), input select, audio adjust (volume, mute, audio input), colour adjust, information, manual image adjust (H/V position, clock, phase, sharpness, video mode adjust, blue light reducer, X-Res Technology), setup menu (language, OSD position, OSD time out, OSD background, opening logo, LED), memory recall
Speakers	2 x 2.5W
Convenience	Kensington-lock™ prepared, DDC2B, Mac OSX

04 MECHANICAL

Display position adjustments	height, pivot (rotation), swivel, tilt
Height adjustment	130mm
Rotation (PIVOT function)	90°
Swivel stand	90°; %3° left; %3° right
Tilt angle	22° up; 5° down
VESA mounting	100 x 100mm

05 ACCESSORIES INCLUDED

Cables	power, HDMI
--------	-------------

Other

quick start guide, safety guide

06 POWER MANAGEMENT**Power supply unit**

internal

Power supply

AC AC - AC V, 100/V, 240Hz

Power usage

19W typical, 0.5W stand by, 0.5W off mode

07 SUSTAINABILITY**Regulations**CE, TÜV-Bauart, VCCI-B, PSE, RoHS support, ErP, ENERGY STAR[®], WEEE, CU, REACH**REACH SVHC**

above 0.1%: Lead

08 DIMENSIONS / WEIGHT**Product dimensions W x H x D**

547.5 x 382.5 (512.5) x 230mm

Weight (without box)

5kg

EAN code

4948570115693

© IIYAMA CORPORATION. ALL RIGHTS RESERVED