



## 01 DEVICE

Supported platforms	Windows, MAC, Chrome, any OS supporting HDMI standard 1.4
HDMI Out	x1
Audio	stereo, radio quality 16bits 48kHz
Frame rate	up to 60 fps depending on environment (FHD)
Output resolution	720x480, 720x576, 1280x720, 1920x1080
Input resolution	Video: 480p, 576p, 720p, 1080p PC timing: 640x480, 800x600, 1024x768, 1280x720, 1920x1080
Wireless	IEEE 802.11ac, 5GHz, IEEE 802.11n, 2.4GHz
Data rate wireless	up to 867Mbps
Authentication protocol	WPA2 (WPA2-PSK (Pre-Shared key) / WPA2-Enterprise)
Security (encryption)	WPA2
Reach	15 m max.

## 02 POWER-MANAGEMENT

Odběr energie:	2.5W typisch
----------------	--------------

## 03 UDRŽITELNOST

Předpisy	CE, RoHS support
----------	------------------

## 04 ROZMĚRY / HMOTNOST

EAN code	4948570032501
----------	---------------

## 05 ENVIRONMENTAL CONDITIONS

Rozsah provozní teploty	0°C - 40°C
-------------------------	------------

Operation humidity	10% - 80%
Rozsah teploty v klidu	- 10°C - 60°C
Storage humidity	5% - 90%

## 06 SOUVÍSEJÍCÍ INFORMACE

Související produkty

[EW-7811UTC](#), [WP.D001HU KIT](#)

*Všechny ochranné známky jsou registrovány a chráněny. Vyhrazené právo na změny. Veškeré ploché panely LCD splňují normu ISO-9241-307:2008 v oblasti počtu vadných pixelů.*

© Iiyama Corporation. All rights reserved