







































#### Immerse yourself in the game with the curved GB3467WQSU Red Eagle with FreeSync **Premium**

Inspired by the curve of the human eye, the 1500R curved VA panel with 165Hz refresh rate, 0.4ms MPRT and the 3440x1440 resolution, guarantees superb image quality and a comfortable and very realistic viewing experience.

The height adjustable stand ensures total flexibility for your perfect screen position. Customize the screen settings using the predefined and custom gaming modes along with the Black Tuner function to give you total control over the dark scenes and make sure details are always clearly visible.



#### **CURVED DESIGN 1500R**

The 1500R curvature of the screen guarantees a realistic and comfortable viewing experience allowing you to really immerse yourself in the game.



#### VA panel technology with 165Hz support and 0.4ms **MPRT**

The monitor guarantees excellent contrast ratio making all the nuances between the light and dark colours clearly visible and provides an outstanding 0.4ms Moving Picture Response Time (MPRT) with 165Hz support.

# 01 DISPLAY CHARACTERISTICS

| Diagonal             | 34", 86.4cm   |
|----------------------|---|
| Panel                | VA LED, matte finish  |
| Curved               | 1500R   |
| Native resolution    | 3440 x 1440 @165Hz (4.9 megapixel UWQHD, DisplayPort)                 |
| Aspect ratio         | 21:9  |
| Panel brightness     | 550 cd/m <sup>2</sup>   |
| Static contrast      | 3000:1  |
| Advanced contrast    | 80M:1   |
| Response time (MPRT) | 0.4ms   |
| Viewing zone         | horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89° |
| Colour support       | 16.7mln 8bit  |
| Horizontal Sync      | 30 - 160kHz   |
| Viewable area W x H  | 797.22 x 333.72mm, 31.4 x 13.1"                                       |
| Pixel pitch          | 0.232mm   |
| Colour               | matte, black  |

## 02

### INTERFACES / CONNECTORS / CONTROLS

| Signal input        | HDMI x2 (v.2.0, max. 3440 x 1440 @100Hz)<br>DisplayPort x2 (v.1.4, max. 3440 x 1440 @165Hz) |
|---------------------|---|
| USB HUB             | x4 (v.3.0 (DC5V, 900mA))  |
| HDCP                | yes   |
| Headphone connector | yes   |



### FEATURES

| Blue light reducer    | yes   |
|-----------------------|---|
| Flicker free          | yes   |
| Adaptive Sync support | HDMI: 3440 x 1440 @48-100Hz, DP: 3440 x 1440 @48-165Hz  |
| HDR                   | 400   |
| OSD languages         | EN, DE, FR, ES, IT, PT, RU, JP, CZ, NL, PL  |
| Control buttons       | joystick controller: Push (Menu), Up, Down, Left (i-Style Colour), Right (Blue Light Reducer) & buttons: Input, Volume+, Volume-, Power   |
| User controls         | picture adjust (contrast, brightness, OD, ACR, ECO, blue light reducer, black tuner, MBR, gamma), input select, audio adjust (volume, mute), store user settings, colour settings (colour temp., 6-Axis, user preset), image adjust (i-Style Colour, X-Res Technology, sharp and soft, HDMI RGB range, direct drive mode, video mode adjust), language, setup menu (OSD H. position, OSD V. position, OSD time, opening logo, HDR, FreeSync Premium, LED, DDC/CI, USB standby mode), display information, reset |
| Speakers              | 2 x 2W  |
| Convenience           | Kensington-lock™ prepared, DDC2B, Mac OSX   |



### MECHANICAL

| Display position adjustments | height, tilt    |
|------------------------------|-----------------|
| Height adjustment            | 130mm           |
| Tilt angle                   | 20° up; 3° down |
| VESA mounting                | 100 x 100mm     |



| Cables | power, USB, HDMI, DP            |
|--------|---------------------------------|
| Other  | quick start guide, safety guide |

## 06 POWER MANAGEMENT

| Power supply unit | internal                                  |
|-------------------|---|
| Power supply      | AC 50 - 60V, 100/240Hz                    |
| Power usage       | 66W typical, 0.5W stand by, 0.5W off mode |

# 07 SUSTAINABILITY

| Regulations   | CE, TÜV-Bauart, EAC, PSE, RoHS support, ErP, WEEE, VCCI, REACH, UKCA |
|---|--|
| Energy efficiency class (Regulation (EU) 2017/1369) | G  |
| REACH SVHC  | above 0.1%: Lead   |

### 08 DIMENSIONS / WEIGHT

| Product dimensions W x H x D | 809.5 x 424.5 (554.5) x 275mm |
|------------------------------|-------------------------------|
| Weight (without box)         | 8.7kg                         |
| Weight (without stand)       | 6.6kg                         |
| EAN code                     | 4948570118694                 |

