



### 27" IPS monitor with USB-C

Equipped with a USB-C connector, the XUB2792HSC allows you to simplify your workspace by using a single cable to power and charge the notebook from the monitor. The IPS matrix offers accurate and consistent colour reproduction with wide viewing angles. The blue light reducer function with flicker free LCD technology reduce eye strain and offer a more comfortable viewing experience. Supplied with a height-adjustable stand featuring swivel function, the XUB2792HSC allows you to easily adjust the screen position to your preferences.



IPS Technology

IPS technology offers higher contrast, darker blacks and much better viewing angles than standard TN technology. The screen will look good no matter what angle you look at it.



USB-C

With one wire you can charge your laptop, connect video (DP-alt mode) and connect with your peripherals through the built in USB 3.0 HUB.

## 01 DISPLAY CHARACTERISTICS

<b>Design</b>	3-side borderless
<b>Diagonal</b>	27", 68.6cm
<b>Panel</b>	IPS LED, matte finish
<b>Native resolution</b>	1920 x 1080 @75Hz (2.1 megapixel Full HD)
<b>Aspect ratio</b>	16:9
<b>Panel brightness</b>	250 cd/m <sup>2</sup>
<b>Static contrast</b>	1000:1
<b>Advanced contrast</b>	80M:1
<b>Response time (GTG)</b>	4ms
<b>Viewing zone</b>	horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89°
<b>Colour support</b>	16.7mIn (sRGB: 99%; NTSC: 72%)
<b>Horizontal Sync</b>	30 - 85kHz
<b>Viewable area W x H</b>	597.8 x 336.3mm, 23.5 x 13.2"
<b>Pixel pitch</b>	0.311mm
<b>Colour</b>	matte, black

## 02 INTERFACES / CONNECTORS / CONTROLS

<b>Signal input</b>	HDMI x1 DisplayPort x1 USB-C x1 (Power delivery 65W)
<b>USB HUB</b>	x2 (v.3.0 (DC5V, 900mA))
<b>HDCP</b>	yes
<b>Headphone connector</b>	yes

## 03 FEATURES

<b>Blue light reducer</b>	yes
<b>Flicker free</b>	yes
<b>OSD languages</b>	EN, DE, FR, ES, IT, RU, JP, CZ, NL, PL
<b>Control buttons</b>	Power, Menu/Select, + / Volume, - / ECO, Exit, Input
<b>User controls</b>	picture adjust (brightness, contrast, ECO, blue light reducer, ACR, OD), colour (colour temp., user preset, i-style colour), OSD (OSD H. position, OSD V. position, OSD rotate, OSD time), language, recall, miscellaneous (sharp and soft, video mode adjust, opening logo, USB BC, MST, display information), input select (input source), audio (volume, mute)
<b>Speakers</b>	2 x 2W
<b>Convenience</b>	Kensington-lock™ prepared, DDC2B, Mac OSX

## 04 MECHANICAL

<b>Display position adjustments</b>	height, swivel, tilt, pivot (rotation both sides)
<b>Height adjustment</b>	130mm
<b>Rotation (PIVOT function)</b>	90°
<b>Swivel stand</b>	90°; 45° left; 45° right
<b>Tilt angle</b>	22° up; 5° down
<b>VESA mounting</b>	100 x 100mm
<b>Cable management system</b>	yes
<b>Operation temperature range</b>	5°C - 35°C

## 05 ACCESSORIES INCLUDED

Cables	power, HDMI, USB-C
Other	quick start guide, safety guide

## 06 POWER MANAGEMENT

Power supply unit	internal
Power supply	AC 100 - 240V, 50/60Hz
Power usage	20W typical, 0.5W stand by, 0.5W off mode

## 07 SUSTAINABILITY

Regulations	TCO Certified, CE, TÜV-GS, EAC, VCCI-B, PSE, RoHS support, ErP, WEEE, REACH, UKCA
Energy efficiency class (Regulation (EU) 2017/1369)	E
REACH SVHC	above 0.1%: Lead

## 08 DIMENSIONS / WEIGHT

Product dimensions W x H x D	612 x 411.5 (541.5) x 230mm
Box dimensions W x H x D	690 x 140 x 451mm
Weight (without box)	6.8kg
Weight (with box)	9.1kg
EAN code	4948570117918

*All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects.*

© IIYAMA CORPORATION. ALL RIGHTS RESERVED