

UNIFIED COMMUNICATIONS

Bluetooth Speakerphone for meeting rooms



The omnidirectional audio pickup from up to 3 meters with intelligent noise reduction and echo cancellation algorithms make the UC SPK01M the perfect choice for medium meeting rooms. Guaranteeing seamless connection via Bluetooth, a USB cable or an audio cable this elegant speaker can be paired with up to 3 devices at the same.



Omnidirectional

The UC SPK01M supports 360-degree omnidirectional audio pickup ensuring every voice in your meeting room is transmitted to the participants joining remotely.



High-quality voice experience

This performance speaker with intelligent noise reduction and echo cancellation algorithms guarantees crystal clear sound for your calls.



Easy set up

Seamless connection via Bluetooth, a USB cable or an audio cable. The speaker is instantly operational after connection.



Multiple device connectivity

Connect up to 3 devices at the same time via Bluetooth, a USB cable and an audio cable.

TEHNICHESKIE-HARAKTERISTIKI

Speaker

Maximum sound pressure level 85dB

Distortion $\leq 1\%$

Signal to noise ratio 75dB

Frequency range 150Hz ~ 16kHz

Microphone

Number of microphone arrays x3

Voice pickup range 3m (radius)

Frequency range 150Hz ~ 7.5kHz

Connectivity & Button operations

USB Type C x1 (Audio In/Out, Charge 5V/2A)

AUX x1 (In/Out, 3.5mm)

Bluetooth 4.2+EDR

Buttons Power, Volume, Bluetooth, Mute, Answer/Hang up

Accessories & Battery

USB (type A to C) cable да

Audio cable yes

Battery capacity 7.4V/2200mAh

Charging wired 5V/2A

Battery life on a single charge 8 hours

Стандарты

Сертификаты CE, RoHS support, ErP, WEEE, REACH

РАЗМЕР / ВЕС

Вес (без упаковки) 0.39кг

EAN код 4948570033034

СОПУТСТВУЮЩАЯ ИНФОРМАЦИЯ

Сопутствующие товары [UC CAM120ULB-1](#), [UC CAM120UL-1](#), [UC CAM180UM-1](#), [UC CAM80UM-1](#), [UC CAM75FS-1](#), [UC SPK01L](#)



Все товарные знаки и торговые марки являются собственностью их владельцев и они защищены. Ошибки и изменения допускаются. Спецификации могут быть изменены без уведомления. Все LCD мониторы соответствуют стандарту ISO-9241-307:2008 по политике битых пикселей. © IIYAMA CORPORATION. ALL RIGHTS RESERVED