

UNIFIED COMMUNICATIONS**Bluetooth Speakerphone for large meeting rooms**

The omnidirectional audio pickup from up to 5 meters with intelligent noise reduction and echo cancellation algorithms make the UC SPK01L the perfect choice for large meeting rooms. Guaranteeing seamless connection via Bluetooth, a USB cable or an audio cable this sleek looking speaker can be paired with up to 3 devices at the same.



Omnidirectional

The UC SPK01L supports 360-degree omnidirectional audio pickup ensuring every voice in your meeting room is transmitted to the participants joining remotely.



High-quality voice experience

This performance speaker with intelligent noise reduction and echo cancellation algorithms guarantees crystal clear sound for your calls.



Easy set up

Seamless connection via Bluetooth, a USB cable or an audio cable. The speaker is instantly operational after connection.



Multiple device connectivity

Connect up to 3 devices at the same time via Bluetooth, a USB cable and an audio cable.

SPECIFICATION

Speaker

Maximum sound pressure level 85dB

Distortion $\leq 4\%$

Signal to noise ratio 80dB

Frequency range 150Hz ~ 16kHz

Microphone

Number of microphone arrays x6

Voice pickup range 5m (radius)

Frequency range 150Hz ~ 8kHz

Connectivity & Button operations

USB Type C x1 (Audio In/Out, Charge 5V/2A)

AUX x1 (In/Out, 3.5mm, DaisyChain)

Bluetooth 4.2+EDR

Buttons Power, Volume, Bluetooth, Mute, Answer/Hang up

Accessories & Battery

Bluetooth receiver ano

Kabel USB (typ A do C) ano

Audio cable ano

Battery capacity 7.4V/2200mAh

Charging wired 5V/2A, wireless 5W

Battery life on a single charge 8 hours

UDRŽITELNOST

Předpisy CE, RoHS support, ErP, WEEE, REACH

ROZMĚRY / HMOTNOST

Váha (bez balení) 0.4kg

EAN code 4948570033041

SOUVÍSEJÍCÍ INFORMACE

Související produkty [UC CAM120ULB-1](#), [UC CAM120UL-1](#), [UC CAM180UM-1](#), [UC CAM80UM-1](#), [UC CAM75FS-1](#), [UC SPK01M](#)



Všechny ochranné známky jsou registrovány a chráněny. Vyhrazené právo na změny. Veškeré ploché panely LCD splňují normu ISO-9241-307:2008 v oblasti počtu vadných pixelů. © IYAMA CORPORATION. ALL RIGHTS RESERVED