

IFP INTERACTIVE DISPLAYS**INFORMACIJE**

65" No-OS Professional Touch Display for Maximum Security and Full IT Control



The ProLite TN6505A-B1AG is a large-format professional touch display, without an operating system, designed for environments where security, reliability and control are non-negotiable. Despite its minimalist structure, the TN6505A is exceptionally easy to use: simply connect your source and it works. The responsive multi-touch panel, 4K UHD resolution and high brightness deliver a precise and professional experience for collaboration, presentations and interactive applications. Built-in annotation allows users to write directly on the screen with a pen, marking up presentations or any on-screen content in real time for clear and effective communication. The TN6505A is the ideal choice for banks, courts, defence organisations, IT departments, universities and other high-security or compliance-driven environments where simplicity, transparency and trust are essential.



OS-Free

- No operating system, where security, reliability and control matter.



Maximum security

With no operating system to manage or update, the display offers a stable, secure solution ideal for environments where data protection and reliability are critical.



Plug & Play simplicity

Designed for ultimate ease of use: plug in your laptop and share your content instantly. No operating system, no complicated configuration.



Estetika koja oplemenjuje svaki prostor

Moderan, minimalistički i osmišljen da unapredi svaki ambijent – ovaj dizajn se savršeno uklapa u učionice i konferencijske sale. Nije samo ekran – to je izjava. Čiste linije, vrhunska završna obrada i prisustvo koje podstiče fokus i profesionalnost, bez preuzimanja pažnje.

01 KARAKTERISTIKE EKRANA

Dijagonala	64.5", 163.9cm
Panel	IPS, AG coating & Anti-Bacteria coating, haze 25%
Osnovna rezolucija	3840 x 2160 (8.3 megapixel 4K UHD)
Format ekrana	16:9
Osvetljenje	500 cd/m ²
Statički kontrast	1200:1
Vreme odziva (GTG)	5ms
Zona gledanja	horizontalno/vertikalno: 178°/178°, desno/levo: 89°/89°, gore/dole: 89°/89°
Horizontalna sinhronizacija	30 - 135KHz
Vidljiva površina Š x V	1428.5 x 803.5mm, 56.2 x 31.6"

02 TOUCH

Touch tehnologija	DeepContrast-IR+
Tačke dodira	40pt (HID, only with supported OS)
Preciznost dodira	+/- 1mm
Interfejs dodira	USB
Podržani operativni sistemi	All iiyama monitors are Plug & Play and compatible with Windows and Linux. For details regarding the supported OS for the touch models, please refer to the driver instruction file available in the downloads section.
Odbijanje dlana	da

03 KONEKTORI / KONTROLE

Ulaz analognog signala	VGA x1 (FHD)
Ulaz digitalnog signala	HDMI x2 (CEC/ARC) DisplayPort x1 USB-C x1 (Power Delivery 65W, DP-Alt, Data, Touch)
Audio ulaz	Mini konektor x3.5 mm
Kontrolni ulaz	RS-232c x1 RJ45 (LAN) x2 ((in/out))
Digitalni izlaz signala	USB-C x1
Audio izlaz	Mini konektor x1 Zvučnici 2 x 20W (Subwoofer 1x 20W)
Monitor kontrolni izlaz	RS-232c x1 IC loop x1 OPS Slot x1 (Intel OPS80 standard)
USB portovi	x1 2.0 (2x 3.2 (USB-B up for touch HDMI1/DP/VGA))
RS-232c	x1
RJ45 (LAN)	x2

04 KARAKTERISTIKE

Integrirani softver	No OS Operating System
PIP (slika u slici)	da
PbP (slika pored slike)	da
Maksimalno neprekidno radno vreme	16/7
Debljina stakla	3.2mm
Tvrdoća stakla	7H
Kućiste (okvir)	metal

05 OPŠTE

OSD jezici	EN, DE, FR, ES, IT, RU, JP, NL
Korisničke kontrole	Color temp., image mode (including eye protection mode), sound mode, no signal standby (Off / 1 min. / 3 min. / 5 min. / 15 min. / 30 min.), meeting mode, time scheduler, key lock, PIP & PBP, brightness / contrast.

06 MEHANIČKI

Orijentacija	pejzaž
Dizajniran bez ventilatora	da
VESA montiranje	600 x 400mm
Opseg radne temperature	0°C - 40°C
Temperatura skladištenja	- 20°C - 60°C

07 UKLJUČENI DODACI

Kablovi	Strujni kabl, HDMI, RS-232c
Ostalo	4x Stylus, Webcam bracket, Wall mount, HDMI 3m, USB 3m, Power

08 UPRAVLJANJE NAPAJANJEM

Napajanje	interna
Potrošnja energije	% 1W tipično, 0.5W stand by, 0.3W isključen

09 ODRŽIVOST

Propisi	CB, CE, TÜV-Bauart, EAC, RoHS podrška, ErP, WEEE, REACH, UKCA
Klasa energetske efikasnosti (Regulation (EU) 2017/1369)	G
REACH SVHC	iznad 0.1%: Olova

10 DIMENZIJE / TEŽINA

Dimenzije proizvoda 1489.1 x 911.8 x 118.6mm
Š x V x D

Težina (bez kutije) 41.1kg

EAN kod 4948570127061

11 KOMPATIBILNI DODACI

Ostalo 4x Stylus, Webcam bracket, Wall mount, HDMI 3m, USB 3m, WP-MEET03M

12 OZNAKA ENERGETSKE EFIKASNOSTI

Potrošnja u OFF 0.3W isključen
modu



All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects. © IIYAMA CORPORATION. ALL RIGHTS RESERVED