

LFD - SIGNAGE DISPLAYS**INFORMATION****55" 4K UHD professional digital signage display with advanced control and connectivity options**

Elevate your visual communication with the LH5560UHS-B2AG and unlock the new possibilities for your business. This 500cd/m² high brightness display is a powerful business tool that takes your marketing and communication efforts to the next level. With its Android 11 OS, [iiSignage²](#) (Content Management Software), Signal FailOver and [EShare](#) features, this display offers a straightforward user experience, making content creation, management, and sharing a breeze.

This ELED VA display consumes significantly less power compared to DLED IPS while maintaining the same level of brightness. Its versatile orientation, sleek design, and 24/7 reliability ensure it seamlessly integrates into any business environment. Whether it's used in retail, corporate, hospitality, or educational settings, the LH5560UHS-B2AG will undoubtedly captivate your audience and leave a lasting impression.



Android OS

Thanks to Android OS, you can easily customize the display to your needs by installing applications directly to it.

4 SIMPLE STEPS

TO REACH YOUR AUDIENCE



iiSignage²

iiSignage² is our digital signage content management platform to easily show and control your content and to manage your displays in a secure way. The Content Management System (CMS) gives you total control of your messaging and advertising remotely and safely.



Signal FailOver

FailOver is a feature which automatically detects input sources. When there is no signal on the default input it will automatically switch to the next available input. FailOver allows customers to prioritize a number of inputs (incl. Browser, Media Player and Custom) and ensures your content is always actively displayed, assuring active content at all times.



Ultra Slim

With 50 percent depth saving over similar models, the jaw-dropping and best in class 40mm total depth display can be installed discretely and elegantly in all areas.

SPECIFIKÁCIÓ

01 KIJELZŐ JELLEMZŐI

Dizájn	Vékony káva
Átló	54.6", 139cm
Panel	VA, Anti-Glare Coated Glass, Hard Coating (3H), haze 25%
Natív felbontás	3840 x 2160 @60Hz (8.3 MegaPixels 4K UHD)
Képarány	16:9
Fényerő	500 cd/m ²
Statikus kontraszt	4000:1
Válaszidő (GTG)	6.5ms
Látótér	horizontális/vertikális: 178°/178°, jobb/bal: 89°/89°, fel/le: 89°/89°
Szín támogatás	1.07G (8 Bits+FRC) (NTSC 87%)
Horizontális szinkronizálás	28 - 160kHz
Látható terület Sz x M	1209.6 x 680.4mm, 47.6 x 28.8"
Káva szélessége (oldal, felső, alsó)	13.3mm, 13.3mm, 15.3mm
Pixel magasság	0.315mm
Káva színe és felülete	fekete, matt

02 INTERFÉSZEK / CSATLAKOZÓK / VEZÉRLŐK

Digitális jelmemenet	HDMI x3 (2.0, max. 3840x2160 @60Hz)
Monitor vezérlő bemenet	RS-232c x1 RJ45 (LAN) x1
Audio kimenet	Mini jack x1 (3.5mm) Hangszórók 2 x 10W
HDCP	1.4 & 2.2
USB portok	x2 (2.0)

03 JELLEMZŐK

Beépített szoftver	Android 11 OS, FailOver, iiSignage ² , EShare
WiFi	igen (Built-in, 802.11ac)
Hardver	CPU: A53*4, GPU: G52 MP2, RAM: 2GB, ROM: 16GB
Extra	Wall mounting kit included (VESA 300x400mm)
Max. non-stop üzemidő	24/7
Anti képmegörzés	igen
Média lejátszás	igen
Ház (káva)	fém (elől)

04 ÁLTALÁNOS

Képernyőn megjelenő nyelvek	EN, DE, FR, ES, IT, CN, RU, JP, CZ, NL, PL, SV, FI, DA, NB
Vezérlőgombok	Power button, Power Indicator, Remote Sensor
Felhasználói vezérlők	picture (brightness, contrast, sharpness, black level, tint, colour, noise reduction, gamma selection, colour temperature, colour control, over scan, picture reset), screen (zoom mode, custom zoom, screen reset), Audio (balance, treble, bass, volume, audio out, maximum volume, minimum volume, mute, audio out sync, speaker setting, audio reset), configuration 1 (switch on state, panel saving, RS232-routing, boot on source, WOL, configuration 1 reset, factory reset), Configuration 2 (OSD timeout, OSD H-Position, OSD V-position, system rotation, information OSD, logo and animation logo setting, animation setting, monitor ID, monitor information, HDMI version, configuration 2 reset), advanced option (IR control, off timer, schedule, HDMI with one wire, HDMI with one wire power off, FailOver, language, OSD transparency, power saving, advanced option reset), Android settings (network & internet, apps & notifications, display, signage display, security, language & input, date & time, about device)
Plug&Play	DDC2B

05 MECHANIKUS

Tájolás	tájkép, portré
Ventilátor nélküli kialakítás	igen
VESA állvány	300 x 400mm
Működési hőmérséklet tartomány	0°C - 40°C
Tárolási hőmérséklet tartomány	- 20°C - 60°C
MTBF	50.000 óra (kivéve háttérvilágítás)

06 TARTOZÉKOKAT TARTALMAZZA

Kábelek	áramellátás (1.8m), HDMI (1.8m), RS-232c (1.8m)
Útmutatók	gyors üzembe helyezési útmutató, biztonsági útmutató
Egyéb	Wall mount bracket, Wall mount guide, Screws, Screw anchors, Stickers for screw holes
Távírányító	igen (elemeket tartalmazza)

07 ENERGIAGAZDÁLKODÁS

Energy Star 8.0 (POn at 230V)	56.2W
Tápegység	belső
Áramellátás	AC 100 - 240V, 50/60Hz
Energiafogyasztás	55W jellemző, 0.5W készenlét, 0.3W kikapcsolva
Áramfogyasztás	0.5W készenlét

08 FENNTARTHATÓSÁG


Előírások	CB, CE, TÜV-Bauart, EAC, RoHS támogatás, ErP, WEEE, HATÓTÁVOLSÁG, UKCA
Energiahatékonysági osztály ((EU) 2017/1369 rendelet)	E



09 MÉRETEK / SÚLY

Termék méretei Sz x H x M	1239.7 x 712.5 x 38.6mm
Doboz méretei Sz x H x M	1390 x 850 x 136mm
Súly (doboz nélkül)	17.6kg
Súly (dobozzal)	22.9kg
EAN kód	4948570125685

10 KAPCSOLÓDÓ INFORMÁCIÓK

Kapcsolódó termékek [ProLite LH3260HS-B1AG](#), [ProLite LH4360UHS-B1AG](#), [ProLite LH5560UHS-B1AG](#), [ProLite LH6560UHS-B1AG](#), [ProLite LH5060UHS-B1AG](#), [ProLite LH6560UHS-B2AG](#), [ProLite LH4360UHS-B2AG](#)







All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects. © **IİYAMA CORPORATION. ALL RIGHTS RESERVED**